

Applicable standard					
Rating	Operating temperature range	-55 °C to +125 °C (95 %RH Max.)	Storage temperature range	-55 °C to +125 °C (95 %RH Max.)	
	Power	-- W	Characteristic impedance	50 Ω(0 to 40 GHz)	
	Peculiarity	----	Applicable cable	----	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	
				QT	AT
CONSTRUCTION					
General examination		Visually and by measuring instrument.		According to drawing.	
Marking		Confirmed visually.			
				X	X
ELECTRICAL CHARACTERISTICS					
Contact resistance		100 mA Max.(DC or 1000 Hz)		Center contact 8 mΩ Max.	
				Outer contact 4 mΩ Max.	
Insulation resistance		500 V DC.		1000 MΩ Min.	
Withstanding voltage		500 V AC for 1 min. current leakage 2 mA Max.		No flashover or breakdown.	
Voltage standing wave ratio		Frequency 0 to 18 GHz.		VSWR 1.1 Max.	
		Frequency 18 to 26.5 GHz		VSWR 1.15 Max.	
		Frequency 26.5 to 40 GHz.		VSWR 1.2 Max.	
Insertion loss		Frequency 0 to 40 GHz.		0.03+0.03√f dB Max. 	
MECHANICAL CHARACTERISTICS					
Contact insertion and extraction forces		φ by steel gauge.		Insertion force --- N Max.	
				Extraction force --- N Min.	
Insertion and extraction forces		Measured by applicable connector.		Insertion force --- N Max.	
				Extraction force --- N Min.	
Mechanical operation		1000 times insertion and extractions.		1)Contact resistance: Center contact 12 mΩ Max. Outer contact 8 mΩ Max. 2)No damage, crack and looseness of parts.	
Vibration		Frequency 10 to 2000 Hz single amplitude 0.75 mm, 196 m/s ² at 10 cycles for 3 directions.		1)No electrical discontinuity of 1 μs. 2)No damage, crack and looseness of parts.	
Shock		1960 m/s ² directions of pulse 6 ms at 3 times for 6 directions.			
Cable clamp strength (Against cable pull)		Using a pulling tester, pull the cable axially at a rate of mm/min. and record the strength at which the cable or connector breaks.		N Min.	
ENVIRONMENTAL CHARACTERISTICS					
Damp heat		Exposed at -10 to +65 °C, 90 to 98 % total 10 cycles.(240 h)		1)Insulation resistance: 100 MΩ Min.  (at high humidity) 2) Insulation resistance: 1000 MΩ Min. (at dry) 3)No damage, crack and looseness of parts.	
Rapid change of temperature		Temperature -65 → — →+125 → — °C Time 30 → 3 →30 →3 min. Under 5 cycles.		No damage, crack and looseness of parts.	
Corrosion salt mist		Exposed in 5 % salt water spray for 48 h.		1.1 Max. (Frequency 0 ~ 18 GHz.) VSWR 1.15 Max.(Frequency18~26.5 GHz.) 1.2 Max. (Frequency 26.5~40 GHz.)	
	Count	Description of revisions		Designed	Checked
	2	DIS-D-00003383		TK.SAWAGUCHI	KY.SHIMIZU
Remark				Approved	KY.SHIMIZU
				Checked	KY.SHIMIZU
				Designed	TY.OZAKI
				Drawn	TY.OZAKI
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				Drawing No.	
				ELC-374783-00-00	
	SPECIFICATION SHEET			Part No.	
	HIROSE ELECTRIC CO., LTD.			Code No.	
				CL338-0099-0-00	
					1/1