



FEMALE FACE VIEW

3-POLE



1 BROWN
3 BLUE
4 BLACK

4-POLE



1 BROWN
2 WHITE
3 BLUE
4 BLACK

POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
4	1200888019	504000E02M050	16.40' +6.50" -0 [5.0M +165.1 -0]

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	OVERMOLD	PVC	YELLOW
4	CABLE 4x0.25 (24AWG) (COPPER STRANDING) 4 CONDUCT. 300V	JACKET: PVC	BLACK

DESCRIPTION
EC NO: WEU2010-0305
DRWN: REISSNER
CHKD: FP
APPR: NSTAUDIG

2010/01/27
2010/02/01

REV

1

QUALITY SYMBOLS

 = 0
 = 0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±---
2 PLACES	±---	±.01
1 PLACE	±0.3	±---
ANGULAR ± --- °		

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE

IN/MM

DRAWN BY
REISSNER

DATE
2010/01/27

CHECKED BY
FP

DATE
2010/01/27

APPROVED BY
NSTAUDIG

DATE
2010/02/01

MATERIAL NO.

SEE TABLE

SIZE
A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE

2:1

DESIGN UNITS

METRIC

 THIRD ANGLE PROJECTION

NC 3/4P FE STR SNAP
24AWG PVC

 **MOLEX INCORPORATED**

DOCUMENT NO.
SD-120088-012

SHEET NO.
1

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP65
OPERATING TEMPERATURE	-30°C TO +80°C (STATIC)
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

