

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Constant voltage source with pluggable connection technology for the generation of a highly precise constant voltage of 15 V and for the supply of sensors without internal power supply. Push-in connection technology.

Commercial data

Item number	1033201
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C404
Product key	CK1444
Catalog page	Page 107 (C-5-2019)
GTIN	4055626537696
Weight per piece (including packing)	108.6 g
Weight per piece (excluding packing)	85 g
Customs tariff number	85437090
Country of origin	DE

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Constant voltage source
Product family	MINI Analog Pro

Data management status

Article revision	03
------------------	----

Insulation characteristics: GB Standard

Overvoltage category	II
Pollution degree	2

Electrical properties

Maximum temperature coefficient	< 0.01 %/K
Maximum transmission error	≤ 0.4 % (of final value)

Electrical isolation Input/output/power supply

Rated insulation voltage	300 V _{rms}
Test voltage	3 kV AC (50 Hz, 60 s)
Insulation	Reinforced insulation according to IEC/EN 61010-1

Supply

Supply voltage range	9.6 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715)
Typical current consumption	< 38.2 mA (24 V) < 79.8 mA (12 V)
Power consumption	< 900 mW (9.6 V DC)

Input data

Signal: Voltage

Voltage input signal	9.6 V DC ... 30 V DC
Transmitter supply voltage	15 V

Output data

Signal: Voltage

Max. voltage output signal	15 V DC
Short-circuit current	> 35 mA

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Output voltage with wire break	15 V
Output current	≤ 30 mA
Ripple	< 20 mV _{PP} (600 Ω)

Connection data

Connection method	Push-in connection
Stripping length	10 mm
Conductor cross section rigid	0.2 mm ² ... 2.5 mm ² (with ferrule) 0.14 mm ² ... 2.5 mm ² (without ferrule)
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12 (flexible)

Ex data

Ex installation (EPL)	Gc Div. 2
-----------------------	--------------

Signaling

Status display	Green LED (supply voltage)
----------------	----------------------------

Dimensions

Width	6.2 mm
Height	109.81 mm
Depth	119.2 mm

Material specifications

Color	gray (RAL 7042)
Housing material	PBT
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (not assessed by UL)
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

Approvals

CE

Certificate	CE-compliant
-------------	--------------

ATEX

Identification	⚡ II 3 G Ex ec IIC T4 Gc
----------------	--------------------------

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Certificate	BVS 20 ATEX E 014X
-------------	--------------------

UKCA Ex (UKEX)

Identification	Ex II 3 G Ex ec IIC T4 Gc
Certificate	PxCIF21UKEX2902004X

IECEX

Identification	Ex ec IIC T4 Gc
Certificate	IECEX BVS 20.0010X

CCC / China-Ex

Identification	Ex nA IIC T4 Gc
Certificate	NEPSI GYJ20.1320X

UL, USA/Canada

Identification	UL 508 Listed
	Class I, Div. 2, Groups A, B, C, D T6
	Class I, Zone 2, Group IIC T6

Shipbuilding approval

Certificate	DNV GL TAA000021E Rev. 1
-------------	--------------------------

DNV GL data

Temperature	B
Humidity	B
Vibration	A
EMC	A
Enclosure	Required protection according to the Rules shall be provided upon installation on board

EMC data

Noise immunity	EN 61000-6-2
Note	When being exposed to interference, there may be minimal deviations.
Electromagnetic compatibility	Conformance with EMC directive
Noise emission	EN 61000-6-4

Standards and regulations

GB Standard

Standards/regulations	GB 3836.1
	GB 3836.8

Mounting

Mounting type	DIN rail mounting
Assembly note	The DIN rail connector can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail.
Mounting position	any

MINI MCR-2-SPS-24-15-PT - Constant voltage source




1033201

<https://www.phoenixcontact.com/us/products/1033201>

Drawings

Block diagram



MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1033201>



EAC

Approval ID: RU*DE.*08.B.01536/19



UL Listed

Approval ID: E238705



CCC

Approval ID: 2021322303003721



cUL Listed

Approval ID: E238705

DNV

Approval ID: TAA000021E



IECEx

Approval ID: IECEx BVS 20.0010X



cUL Listed

Approval ID: E196811



UL Listed

Approval ID: E196811



ATEX

Approval ID: BVS 20 ATEX E 014X



NEPSI-EX

Approval ID: GYJ20.1320X

cULus Listed

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

cULus Listed

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Classifications

ECLASS

ECLASS-11.0	27040701
ECLASS-13.0	27210192
ECLASS-12.0	27040701

ETIM

ETIM 9.0	EC002498
----------	----------

UNSPSC

UNSPSC 21.0	39121000
-------------	----------

MINI MCR-2-SPS-24-15-PT - Constant voltage source



1033201

<https://www.phoenixcontact.com/us/products/1033201>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7)
SCIP	9b057950-7862-4212-aef1-e01d5f7467d5

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com