

10		9		8	7		6		5	4	3	2	1
CIRCUITS	PART NUMBER	ENGINEERING NUMBER	COLOR	DIM. "A"		DIM. "B"							
				MM	IN	MM	IN						
2	397701002	MX-CBF020R8	GREEN	7.00	[.276]	3.50	[.138]						
3	397701003	MX-CBF030R8	GREEN	10.50	[.413]	7.00	[.276]						
4	397701004	MX-CBF040R8	GREEN	14.00	[.551]	10.50	[.413]						
5	397701005	MX-CBF050R8	GREEN	17.50	[.689]	14.00	[.551]						
5	397701006	MX-CBF050R8-0N	BLACK	17.50	[.689]	14.00	[.551]						
6	397701007	MX-CBF060R8	GREEN	21.00	[.827]	17.50	[.689]						
7	397701008	MX-CBF070R8	GREEN	24.50	[.965]	21.00	[.827]						
7	397701009	MX-CBF070R8-0B	BLUE	24.50	[.965]	21.00	[.827]						
8	397701010	MX-CBF080R8	GREEN	28.00	[1.102]	24.50	[.965]						
9	397701011	MX-CBF090R8	GREEN	31.50	[1.240]	28.00	[1.102]						
10	397701012	MX-CBF100R8	GREEN	35.00	[1.378]	31.50	[1.240]						
11	397701013	MX-CBF110R8	GREEN	38.50	[1.516]	35.00	[1.378]						
12	397701014	MX-CBF120R8	GREEN	42.00	[1.654]	38.50	[1.516]						

NOTES:


- 1) MATERIAL:
- A) BODY: PA66 V-0

B) SCREW: BRASS



C) CLAMP: BRASS

D) SPRING/PIN: BRASS
- 2) RATING: 300V (UL)
- 3) WIRE: 14-30AWG STRANDED 11A
- 14-30AWG SOLID 9A
- 4) OPERATING TEMPERATURE RANGE: -40°C TO +110°C
- 5) CONTACT RESISTANCE: <15mΩ
- 6) WIRE STRIP LENGTH: 105 - 11.5 MM(.41-.45IN)
- 7) UL FILE: E48521

DOCUMENT STATUS	P1	RELEASE DATE	2023/06/30	22:29:39
-----------------	----	--------------	------------	----------





"A"



.138
[3.50]

"B"



FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
	DIMENSION UNITS		SCALE		CURRENT REV DESC: NEW RELEASE			molex			
= 0	INCH/MM		2:1								
= 0	GENERAL TOLERANCES (UNLESS SPECIFIED)				SPRING CONNECTOR FEMALE PITCH 3.50 (.138")						
= 0	MM		INCH								
DIVISIONAL SYMBOLS	4 PLACES		±	---	±	---	EC NO: 754061				
	3 PLACES		±	---	±	.010	DRWN: ABENJAMINLW 2023/06/20				
	2 PLACES		±	0.25	±	---	CHK'D: DACHAMMER 2023/06/20				
	1 PLACE		±	---	±	---	APPR: JFMURPHY 2023/06/30				
	0 PLACES		±	---	±	---	INITIAL REVISION:				
	ANGULAR TOL		±	0.5 °	DRWN: ABENJAMINLW 2023/06/20						
					APPR: JFMURPHY 2023/06/30						
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						THIRD ANGLE PROJECTION		DRAWING		SERIES	
								B-SIZE		39770	
								MATERIAL NUMBER		CUSTOMER	
								SEE CHART		GENERAL MARKET	
										SHEET NUMBER	
										1 OF 1	




10		9		8		7			
CIRCUITS	PART NUMBER	ENGINEERING NUMBER	COLOR	DIM. "A"		DIM. "B"			
				MM	IN	MM	IN		
2	397700005	MX-CBF020RT	GREEN	7.62	[.300]	3.81	[.150]		
2	397700001	MX-CBF020RT-0N	BLACK	7.62	[.300]	3.81	[.150]		
3	397700006	MX-CBF030RT	GREEN	11.43	[.450]	7.62	[.300]		
4	397700007	MX-CBF040RT	GREEN	15.24	[.600]	11.43	[.450]		
4	397700002	MX-CBF040RT-0N	BLACK	15.24	[.600]	11.43	[.450]		
5	397700008	MX-CBF050RT	GREEN	19.05	[.750]	15.24	[.600]		
5	397700009	MX-CBF050RT-0N	BLACK	19.05	[.750]	15.24	[.600]		
6	397700010	MX-CBF060RT	GREEN	22.86	[.900]	19.05	[.750]		
6	397700003	MX-CBF060RT-0N	BLACK	22.86	[.900]	19.05	[.750]		
7	397700011	MX-CBF070RT	GREEN	26.67	[1.050]	22.86	[.900]		
7	397700012	MX-CBF070RT-0B	BLUE	26.67	[1.050]	22.86	[.900]		
8	397700013	MX-CBF080RT	GREEN	30.48	[1.200]	26.67	[1.050]		
8	397700004	MX-CBF080RT-0N	BLACK	30.48	[1.200]	26.67	[1.050]		
9	397700014	MX-CBF090RT	GREEN	34.29	[1.350]	30.48	[1.200]		
10	397700015	MX-CBF100RT	GREEN	38.10	[1.500]	34.29	[1.350]		
11	397700016	MX-CBF110RT	GREEN	41.91	[1.650]	38.10	[1.500]		
12	397700017	MX-CBF120RT	GREEN	45.72	[1.800]	41.91	[1.650]		

NOTES:



- 1) MATERIAL:
- A) BODY: PA66 V-0
- B) SCREW: BRASS
- C) CLAMP: BRASS
- D) SPRING/PIN: BRASS
- 2) RATING: 300V (UL)
- 3) WIRE: 14-30AWG STRANDED 11A
- 14-30AWG SOLID 9A
- 4) OPERATING TEMPERATURE RANGE: -40°C TO +110°C
- 5) CONTACT RESISTANCE: <15mΩ
- 6) WIRE STRIP LENGTH: 105 - 11.5 MM(.41-.45IN)
- 7) UL FILE: E48521

DOCUMENT STATUS	P1	RELEASE DATE	2023/06/30	22:29:38
-----------------	----	--------------	------------	----------

A2



.150 PITCH
[3.81]



FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
	DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED PART NUMBER CHART WITH NEW PNS			molex				
	INCH/MM		2:1									
	GENERAL TOLERANCES (UNLESS SPECIFIED)				SPRING CONNECTOR FEMALE PITCH 3.81 (.150")							
					PRODUCT CUSTOMER DRAWING							
					DOCUMENT NUMBER SD-39770-001			DOC TYPE PSD	DOC PART 001	REVISION A2		
					MATERIAL NUMBER SEE CHART			CUSTOMER GENERAL MARKET		SHEET NUMBER 1 OF 1		
DIVISIONAL SYMBOLS					EC NO: 754063 DRWN: ABENJAMINLW 2023/06/16 CHK'D: DACHAMMER 2023/06/20 APPR: JFMURPHY 2023/06/30			INITIAL REVISION: DRWN: BRUPERT 2016/09/09 APPR: JFMURPHY 2016/10/07				
					THIRD ANGLE PROJECTION			DRAWING B-SIZE	SERIES 39770			
					DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							