



Catalog No. 2TLA020070R4700

Description: PLUTO S20 V2, SAFETY-PLC

UPC No 7320500410554

Home > Machine Safety > Programmable Safety Controllers

Pluto is a cost effective, powerful and compact safety PLC for all machine safety applications. Most safety devices on the market can be connected directly to Pluto and multiple safety sensors can be connected to a single input and still achieve the highest safety level. Programming is done easily in the accompanying software Pluto Manager. Safety PLC. Totally 20 I/O: 8 failsafe inputs + 8 non-failsafe outputs/failsafe inputs + 2 individually failsafe relay outputs + 2 individually failsafe transistor outputs. (Without Pluto safety bus). NOTE: Version 2 hardware/processor.

Descriptors	
Category	Programmable Safety Controllers
Specifications	
Supply Voltage	24VDC
Product Main Type	Pluto
With Safety Bus	No
Safe Outputs	2NO Failsafe (Relay) + 2 Failsafe (Transistor)
Safe inputs/non-failsafe outputs/safe analog inputs	8 failsafe inputs + 8 non-failsafe outputs/failsafe inputs
Product Class	Safety Programmable Logic Controllers
Degree of Protection	IP20(Terminals) and IP40(Enclosure)
ETIM 4 ETIM 5.0	EC001449 - Device for monitoring of safety-related circuits EC001449 - Device for monitoring of safety-related circuits
Classifications	
ETIM 5.0	
ETIM 6.0	EC000236 - PLC CPU-module
ETIM 7	EC000236 - PLC CPU-module
ETIM 8 (Etim8)	EC000236 - PLC CPU-module
Dimensions	
Product Net Depth / Length	120 mm
Product Net Height	84 mm
Product Net Width	45 mm
Product Net Weight	0.39kg
Safety Information	
Performance Level	Up to e

electrification.us.abb.com Created on: 09/19/2024

electrification.us.abb.com Created on: 09/19/2024