

380-018

EMI/RFI Non-Environmental Backshell


with Strain Relief

Type E - Rotatable Coupling - Low Profile


CONNECTOR DESIGNATORS A-F-H-L-S

ROTATABLE COUPLING


TYPE E INDIVIDUAL AND/OR OVERALL SHIELD TERMINATION




Length $\pm .060$ (1.52)
Minimum Order Length 2.0 Inch
(See Note 4)



STYLE 2
(STRAIGHT
See Note 1)




STYLE 2
(45° & 90°
See Note 1)




-445

Now Available
with the "NESTOR"
Glenair's Non-Detent, Spring-
Loaded, Self-Locking Coupling.
Add "-445" to Specify This
AS85049 Style "N" Coupling
Interface.


STYLE H
Heavy Duty
(Table X)




STYLE A
Medium Duty
(Table XI)



STYLE M
Medium Duty
(Table XI)



STYLE D
Medium Duty
(Table XI)



380-018
EMI/RFI Non-Environmental Backshell
with Strain Relief
Type E - Rotatable Coupling - Low Profile



See inside back cover fold-out or pages 13 and 14 for unabridged Tables I and II.

TABLE III: ELBOW DIMENSIONS

Shell Size Conn. Desig. A-F-L-S H		E Max	F Max	G Max	H Max
08	09	.520 (13.2)	1.680 (47.2)	.477 (12.7)	1.730 (43.9)
10	11	.615 (15.6)	1.800 (45.7)	.540 (13.7)	1.730 (43.9)
12	13	.630 (16.0)	1.820 (46.2)	.602 (15.3)	1.790 (45.5)
14	15	.720 (18.3)	1.890 (48.0)	.665 (19.6)	1.880 (47.8)
16	17	.905 (23.0)	1.980 (50.3)	.758 (19.2)	1.990 (50.5)
18	19	.995 (25.3)	2.150 (54.6)	.946 (24.0)	2.180 (55.4)
20	21	.995 (25.3)	2.150 (54.6)	.946 (24.0)	2.180 (55.4)
22	23	1.145 (29.1)	2.260 (57.4)	1.040 (26.4)	2.330 (59.2)
24	25	1.145 (29.1)	2.260 (57.4)	1.040 (26.4)	2.330 (59.2)

TABLE II: STANDARD FINISHES

GLENAIR SYMBOL	FINISH
B	Cadmium Plate, Olive Drab
M	Electroless Nickel
NF	Cadmium Plate, Olive Drab Over Electroless Nickel
See Inside Back Cover for Additional Finish Options	

TABLE X: CABLE ENTRY

Dash No.	T Max	V Max	Cable Range	
			Min	Max
04	.780 (19.8)	.957 (24.3)	.125 (3.2)	.312 (7.9)
06	.780 (19.8)	1.145 (29.1)	.250 (6.4)	.437 (11.1)
08	.780 (19.8)	1.332 (33.8)	.312 (7.9)	.562 (14.3)
10	.780 (19.8)	1.332 (33.8)	.350 (8.9)	.625 (15.9)
12	.811 (20.6)	1.551 (39.4)	.500 (12.7)	.750 (19.1)
16	.905 (23.0)	1.770 (45.0)	.625 (15.9)	.937 (23.8)
20	1.092 (27.7)	2.113 (53.7)	.875 (22.2)	1.250 (31.8)
24	1.124 (28.5)	2.363 (60.0)	1.000 (25.4)	1.375 (34.9)
28	1.399 (35.5)	2.770 (70.4)	1.250 (31.8)	1.625 (41.3)
32	1.399 (35.5)	3.020 (76.7)	1.437 (36.5)	1.875 (47.6)

1. When maximum cable entry (page 21) is exceeded, Style 2 will be supplied. Dimensions E, F, G and H will not apply. Please consult factory.
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
4. Consult factory for shorter lengths on straight backshells.
5. Designate Symbol T for 3 ring termination of individual and overall braid. Designate D for standard 2 ring termination of individual or overall braid.

TABLE XI: CABLE ENTRY

Dash No.	W Max	X Max	Y Max	Z Max	Cable Range	
					Min **	Max
03*	.437 (11.1)	.760 (19.3)	.843 (21.4)	.630 (16.0)	.156 (4.0)	.250 (6.4)
04*	.437 (11.1)	.760 (19.3)	.906 (23.0)	.755 (19.2)	.188 (4.8)	.312 (7.9)
06*	.500 (12.7)	.760 (19.3)	1.093 (27.8)	.942 (23.9)	.281 (7.1)	.438 (11.1)
08	.563 (14.3)	.760 (19.3)	1.187 (30.1)	1.067 (27.1)	.344 (8.7)	.562 (14.3)
10	.563 (14.3)	.760 (19.3)	1.281 (32.5)	1.192 (30.3)	.375 (9.5)	.625 (15.9)
12	.563 (14.3)	.760 (19.3)	1.500 (38.1)	1.380 (35.1)	.438 (11.1)	.750 (19.1)
16	.656 (16.7)	1.073 (27.3)	1.719 (43.7)	1.535 (39.0)	.562 (14.3)	.938 (23.8)
20	.656 (16.7)	1.323 (33.6)	2.062 (52.4)	1.848 (46.9)	.750 (19.1)	1.250 (31.8)
24	.656 (16.7)	1.323 (33.6)	2.312 (58.7)	2.255 (57.3)	.781 (19.8)	1.375 (34.9)
28	1.188 (30.2)	1.572 (39.9)	2.719 (69.1)	2.505 (63.6)	.969 (24.6)	1.625 (41.3)
32*	1.187 (30.1)	1.572 (39.9)	2.969 (75.4)	2.755 (70.0)	1.125 (28.6)	1.875 (47.6)
40*	1.125 (28.6)	1.572 (39.9)	3.531 (89.7)	3.255 (82.7)	1.469 (37.3)	2.375 (60.3)

* Not available in Style M clamp.

** Not Applicable Style D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Glenair:

[380AS018N1604DA3](#) [380HA018M1104TH](#) [380HS018M0904TH6](#) [380HS018M1308TH3](#) [380HS018M1704DH3](#)
[380HS018M1106DH3](#) [380HS018M1308DH3](#) [380HS018M2106DH3](#) [380AA018NF1408DH](#) [380AS018M1006TA3](#)
[380AS018M1206DA3](#) [380AS018N1606DA3](#) [380AS018N1606DH4](#) [380AS018N2008DA3](#) [380AS018N2208DA3](#)
[380AS018NF1810TM3](#) [380FA018N0806DA](#) [380FA018N1006DA](#) [380FA018N1210DA](#) [380FA018N1608DA](#)
[380FB018M1812TH](#) [380HA018M1104TA](#) [380HA018NF1312TA](#) [380HS018B1516TD3](#) [380HS018B2310TD3](#)
[380HS018M0904DA3](#) [380HS018M0904TA3](#) [380HS018M1104DA3](#) [380HS018M1106TA3-63](#) [380HS018M1306DA3](#)
[380HS018M1306TA3](#) [380HS018M1308TA3](#) [380HS018M1310TA3](#) [380HS018M1510TA3](#) [380HS018M1712TA3](#)
[380HS018M2116TA3](#) [380HS018M2316TA3](#) [380HS018M2516TA3](#) [380HS018N1106DA3](#) [380HS018N1304DA3](#)
[380HS018N1306DA3](#) [380HS018N1506DA3](#) [380HS018N1508DA3](#) [380HS018N1510DA3](#) [380HS018N1706DA3](#)
[380HS018N1710DA3](#) [380HS018N1910DA3](#) [380HS018N2108DA3](#) [380HS018NF0904TA3](#) [380HS018NF1712TA3](#)
[380HS018NF2316DD3-62](#) [380FA018N1616DA](#) [380HS018B1116TA4](#) [380HS018B1916TA4](#) [380HS018B2112TA4](#)
[380AS018N1406DA3](#) [380HS018N2110DA3](#) [380HS018NF1706TH3](#) [380AS018N2012DA3](#) [380FB018NF2416TH](#)
[380HA018M1308TH](#) [380HA018M2316TH](#) [380HA018N2510TM](#) [380HA018NF1508TH](#) [380HA018NF1710DA](#)
[380HB018M1506TH](#) [380HS018M0903TA3](#) [380HS018M1104TA4](#) [380HS018M1106TA3](#) [380HS018M1506DA3](#)
[380HS018M1506TA3](#) [380HS018M1716DA3](#) [380HS018M1916TA3](#) [380HS018M2116TA6](#) [380HS018M2306TA3](#)
[380HS018M2520TH6](#) [380HS018N2510TM4](#) [380HS018NF1108DM4](#) [380HS018NF1508TA3](#) [380HS018NF1510TA3](#)
[380HS018NF1510TM3](#) [380HS018NF2512DM4](#) [380HS018M2104DH3](#) [380FA018N1206DA](#) [380HA018N1506DA](#)
[380AS018NF0806TA4](#) [380AS018NF1606TA3](#) [380HB018M2116TA](#) [380HS018M1308DA3](#) [380HS018M1512TA3](#)
[380HS018M2116TA4](#) [380HS018M2316TH6](#) [380HS018M2320TA3](#) [380HS018M2512DA3](#) [380HS018NF1104TA3](#)
[380HS018NF1106TA4](#) [380HS018NF1306TA3](#) [380HS018NF1308TH3](#) [380AS018NF1406TA3](#) [380HA018M2116TA](#)