

AS85049/17 Straight EMI/RFI Environmental Backshell



AS85049

CONNECTOR DESIGNATOR:

F MIL-DTL-38999 Series I and II

Finish

N = Electroless Nickel

W = 1,000 Hr. Cadmium Olive Drab
over Electroless Nickel

X = Aluminum, Nickel Fluorocarbon Polymer

Z = Aluminum, Zinc-Nickel, Black

M85049/17

10

N

03

A

**Basic
Part Number**


**Dash Number
(Table I)**

**Clamp Size
(Table III)**

**Length Code
(Table IV)
Omit for Standard**

**TABLE I: Shell Size,
Thread and Dimensions**

Dash No.	Shell Size Series I	Shell Size Series II	A Thread Class 2B	B Dia Max
08	09	08	.438 - 28 UNEF	.570 (14.5)
10	11	10	.562 - 24 UNEF	.700 (17.8)
12	13	12	.688 - 24 UNEF	.830 (21.1)
14	15	14	.813 - 20 UNEF	.950 (24.1)
16	17	16	.938 - 20 UNEF	1.080 (27.4)
18	19	18	1.063 - 18 UNEF	1.200 (30.5)
20	21	20	1.188 - 18 UNEF	1.330 (33.8)
22	23	22	1.313 - 18 UNEF	1.450 (36.8)
24	25	24	1.438 - 18 UNEF	1.580 (40.1)



**TABLE II: Shell Size
and Clamp Size**

Dash No.	Shell Size Series I	Shell Size Series II	Clamp Size Min	Clamp Size Max
08	09	08	01	02
10	11	10	01	03
12	13	12	02	04
14	15	14	02	05
16	17	16	02	06
18	19	18	03	07
20	21	20	03	08
22	23	22	03	09
24	25	24	04	10

TABLE III: Clamp Size, Cable Range and Dimensions

Clamp Size	Cable Range Min	Cable Range Max	E Max	F Max
01	.062 (1.6)	.125 (3.2)	.781 (19.8)	1.250 (31.8)
02	.125 (3.2)	.250 (6.4)	.969 (24.6)	1.250 (31.8)
03	.250 (6.4)	.375 (9.5)	1.062 (27.0)	1.250 (31.8)
04	.375 (9.5)	.500 (12.7)	1.156 (29.4)	1.250 (31.8)
05	.500 (12.7)	.625 (15.9)	1.250 (31.8)	1.312 (33.3)
06	.625 (15.9)	.750 (19.1)	1.375 (34.9)	1.375 (34.9)
07	.750 (19.1)	.875 (22.2)	1.500 (38.1)	1.500 (38.1)
08	.875 (22.2)	1.000 (25.4)	1.625 (41.3)	1.625 (41.3)
09	1.000 (25.4)	1.125 (28.6)	1.750 (44.5)	1.625 (41.3)
10	1.125 (28.6)	1.250 (31.8)	1.875 (47.6)	1.625 (41.3)

TABLE IV: Length Code

Length Code	Available Shell Sizes	Length
Standard	08 - 24	1.500 (38.1)
A	08 - 24	2.500 (63.5)
B	14 - 24	3.500 (88.9)
C	20 - 24	4.500 (114.3)

APPLICATION NOTES

- For complete dimensions see the applicable Military Specification.
- Metric dimensions (mm) are in parentheses.
- Cable Range is defined as the accommodation range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.

Dimensions in inches (millimeters) and are subject to change without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Glenair:

[M85049/1720W05](#) [M85049/1724W04A](#) [M85049/1718W03](#) [M85049/1722W08A](#) [M85049/1720N03](#)
[M85049/1712W03A](#) [M85049/1714W03A](#) [M85049/1714W04A](#) [M85049/1716N04](#) [M85049/1716N05](#) [M85049/1716W02](#)
[M85049/1716W04A](#) [M85049/1716W06B](#) [M85049/1718W03A](#) [M85049/1718W06](#) [M85049/1718W07](#)
[M85049/1718W07A](#) [M85049/1720W03A](#) [M85049/1720W04A](#) [M85049/1720W08](#) [M85049/1722W06](#)
[M85049/1722W06B](#) [M85049/1708W02](#) [M85049/1710N02](#) [M85049/1710N03](#) [M85049/1710W03](#) [M85049/1712N02](#)
[M85049/1712N04](#) [M85049/1712N04A](#) [M85049/1712W02](#) [M85049/1712W03](#) [M85049/1712W04](#) [M85049/1712W04A](#)
[M85049/1714N02](#) [M85049/1714N04](#) [M85049/1714N05A](#) [M85049/1714W02](#) [M85049/1714W03](#) [M85049/1714W04](#)
[M85049/1714W05](#) [M85049/1714W05A](#) [M85049/1716N06](#) [M85049/1716N06A](#) [M85049/1716W03](#) [M85049/1716W04](#)
[M85049/1716W05](#) [M85049/1716W06](#) [M85049/1716W06A](#) [M85049/1718N03](#) [M85049/1718W04](#) [M85049/1718W04A](#)
[M85049/1720N05](#) [M85049/1720N05A](#) [M85049/1720W03](#) [M85049/1720W05A](#) [M85049/1720W07A](#)
[M85049/1720W08A](#) [M85049/1722N05A](#) [M85049/1722W04](#) [M85049/1722W05](#) [M85049/1722W05A](#)
[M85049/1722W07](#) [M85049/1722W08](#) [M85049/1722W09](#) [M85049/1722W09A](#) [M85049/1724N05A](#) [M85049/1724N06](#)
[M85049/1724N07](#) [M85049/1724N07B](#) [M85049/1724N08A](#) [M85049/1724W05A](#) [M85049/1712N03](#) [M85049/1710W02](#)
[M85049/1716N02](#) [M85049/1712N04B](#) [M85049/1712W04B](#)