




MAPX	MODIFICATION	DATE

Note:

1.Material:

1.1,Housing: High temperature thermoplastic with/black G/F,UL94v-0

1.2,Contact: copper alloy,t=0.25mm

1.3,Shell: copper/Ferroalloy alloy,t=0.30mm

2.Specification:

2.1,Current rating:1.5A Max.

2.2,Dielectric withstanding voltage: 100 V(ac) for 1 min.

2.3,Contact resistance: 30 mΩ Max.

2.4,Insulation resistance: 100 MΩ Min.

2.5,Total mating force: 3.57 Kgf Max.

2.6,Total unmating force: 1.0 Kgf Min.

3.Finish:

3.1,Contact: Plated Golg in Mating Area: Tin On Solder Talls

Shell: Nickel Plating

4.Environmental:

4.1,Temperature range: -55°C~85°C

PART ON:

907-222AXXX1Y1XX

—电镀规格: 02, 镀金1u" 04, 镀金3u" 07, 镀金15u" 08, 镀金30u"

—端子材质: 1, 青铜 2, 磷铜

—端子规格: D, 90度 Y, 180度 S, SMT贴板

—塑胶形态: 1, 双层短体 2, 双层半包

—塑胶颜色: 01, 白色 02, 黑色 03, 本色

—塑胶材质: 1, PBT 2, LCP 3, PA9T 4, PPA 5, PA6T

—对插方向: A, 正向 B, 反向

—外壳材质: 1, 铁壳 2, 铜壳

—插口类型: 1, 有边平弹 2, 无边平弹

—外壳脚型: 1, 弯脚 2, 直脚 3, 无脚 4, 鱼叉脚

—类别: 双层系列

P. C. B LAYOUT

产品图 PRODUCT CHART DWG		深圳市精拓金电子有限公司							
公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	YANG	制图料号 PRODUCT PART NO.	907-322A1051Y10210		
X.	±0.30	X.	±5.°	比例 SCALE	审核 CHKD	产品名称 PRODUCT NO.	AF大电流180度10.5双层无脚无边平弹 铜壳PBT蓝胶		
.X	±0.25	.X	±2.°	日期 DATE	2019. 11. 23	角法 VIEW	版本 VER	AO	
.XX	±0.15	.XX	±1.°	核准 APPD	黄国荣				
.XXX	±0.10	.XXX	±0.5°						