### FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 178471-2

Receptacle, Plug, 1 Position, Straight, UL 94V-0, Gray, PBT, Contact Mating Retention, Mating Alignment, FASTIN-FASTON 250, Crimp

Terminal Housings

View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings











Terminal Type: Receptacle

Connector & Housing Type: Plug

Number of Positions: 1

Terminal Orientation: Straight
UL Flammability Rating: UL 94V-0

### **Features**

### **Product Type Features**

Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Plug
Configuration Features	
Number of Positions	1
Body Features	
Primary Product Color	Gray
Contact Features	
Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With
Mechanical Attachment	

Double Lock

Mating Retention Type



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT
Dimensions	
Product Width	25 mm[.984 in]
Product Length	8 mm[.314 in]
Product Height	10 mm[.394 in]
Usage Conditions	
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	100
Packaging Method	Bag

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts






FF 250 PLUG HSG 1P NYLON BLACK









# Also in the Series | FASTIN-FASTON 250









# Customers Also Bought



















### **Documents**

### **Product Drawings**

**DOUBLE LOCK CONNECTOR 250 ASSEMBLY** 

Japanese

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_178471-2\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_178471-2\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_178471-2\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

**Product Specification** 

Japanese

.250 SERIES DOUBLE LOCK CONNECTOR

Japanese

**Instruction Sheets** 

Instruction Sheet (U.S.)

Japanese

Instruction Sheet (U.S.)

English