

2707958

https://www.phoenixcontact.com/us/products/2707958

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Kit consisting of COMBICON header and screw connectors for 6x3 positions (18-pos.), color:



### Commercial data

Item number	2707958
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AC08
Product key	ACHADB
GTIN	4017918906115
Weight per piece (including packing)	41.5 g
Weight per piece (excluding packing)	39.94 g
Customs tariff number	85366990
Country of origin	DE



2707958

https://www.phoenixcontact.com/us/products/2707958

#### Set consists of

#### MSTBO 2,5/3-G1L - PCB header

1861028

https://www.phoenixcontact.com/us/products/1861028



PCB headers, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, contact connection type: Pin, number of rows: 1, number of positions: 3, product range: MSTBO 2,5/..-G1L, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, locking: without, type of packaging: packed in cardboard, Product with pin output on left side

#### MSTBO 2,5/3-G1R - PCB header

1861031

https://www.phoenixcontact.com/us/products/1861031



PCB headers, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, contact connection type: Pin, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTBO 2,5/..-G1R, pitch: 5 mm, connection method: pluggable, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, locking: without, type of packaging: packed in cardboard, Product with pin output on right side



2707958

https://www.phoenixcontact.com/us/products/2707958

#### MSTBT 2,5/3-ST - PCB connector

1779848

https://www.phoenixcontact.com/us/products/1779848



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTBT 2,5/..-ST, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard



2707958

https://www.phoenixcontact.com/us/products/2707958

### Technical data

### Product properties

Product type	PCB headers
Number of positions	3
Pitch	5 mm
Mounting flange	without
Pin layout	Linear pinning

### Electrical properties

Rated voltage (II/2)	400 V
Rated voltage (III/2)	320 V
Rated surge voltage (II/2)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (III/3)	4 kV

### Mounting

Mounting type	Soldering
Pin layout	Linear pinning

### Material specifications

Color (Housing)	green (RAL 6021)
Insulating material	PA
Contact surface material	Sn

#### **Dimensions**

	_
Pitch	5 mm



2707958

https://www.phoenixcontact.com/us/products/2707958

### **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2707958

VDE Zeichengenehmigung Approval ID: 40050648				
	Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
	250 V	8 A	-	-



2707958

https://www.phoenixcontact.com/us/products/2707958

### Classifications

UNSPSC 21.0

#### **ECLASS**

ECLASS-11.0	27460201
ECLASS-12.0	27460201
ECLASS-13.0	27460201
ETIM	
ETIM 9.0	EC002637
UNSPSC	

39121400



2707958

https://www.phoenixcontact.com/us/products/2707958

## Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



2707958

https://www.phoenixcontact.com/us/products/2707958

#### Accessories

CR MSTBO-G1 - Coding section

2199618

https://www.phoenixcontact.com/us/products/2199618

Coding section, inserted into the recess in the header or the inverted plug, red insulating material



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com