



PennEngineering
Corporate Headquarters – Danboro, PA

5190 Old Easton Rd.

Danboro, PA 18916

Phone: 215-766-8853

Toll-Free Phone: 1-800-237-4736 (U.S. only)


Email: info@pemnet.com

Website: www.pemnet.com

Part # SL-440-1ZI, TRI-DENT® Locknuts - Type SL - Unified


Type SL self-locking nuts are designed with a unique and economical TRI-DENT® locking feature, which meets demanding locking performance requirements.

- 3 cycle locking performance. Achieved using steel socket head cap screws, 180 ksi / property



Specifications

Thread Size	.112-40 (#4-40)
Thread Code	440
Shank Code	1
A (Shank) Max.	0.038 in
Min. Sheet Thickness	.040 in
Hole Size in Sheet + .003 - .000	.166 in
C Max.	.165 in
E ± .010	.250 in
T ± .010	.070 in
Min. Dist. Hole C/L to Edge	.19 in
For Use in Sheet Hardness	HRB 80 / HB 150 or less
Thread Specification	Internal, ASME B1.1, 2B
Fastener Material	Heat-Treated Carbon Steel



Standard Finish	Zinc plated per ASTM B633,	SC1 (5µm), Type III, colorless
CAD Supplier	PennEngineering® (PEM®)	