

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQW43FT220M0H# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LQW43FT220M0H%2

"#"at the end indicates the package specification code.

Wide frequency band, high inductance, for power line.















< List of part numbers with package codes >

LQW43FT220M0HB

LQW43FT220M0HK

LQW43FT220M0HL




Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment, Automotive
	infotainment/comfort equipment,
	Automotive powertrain/safety equipment,
	Medical equipment [GHTF A/B/C]
	except for implant & surgery & auto
	injector,Industrial Equipment
Specific	Please refer to Our Website and
Applications	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.
Recommended	Automotive powertrain/safety equipment,
Applications	PoC [Power over Coax]



Appearance & Shape





1 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQW43FT220M0H# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LQW43FT220M0H%2

"#"at the end indicates the package specification code.



References

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	100
К	330Embossed Tape	1500
L	180Embossed Tape	400

Mass (typ.)	
1 piece	0.209g

2 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQW43FT220M0H# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LQW43FT220M0H%2

"#"at the end indicates the package specification code.



Specifications

L size	4.5±0.2mm
W size	3.2±0.2mm
T size	3.5±0.2mm
Size code inch (mm)	1812 (4532)
Inductance	22µH±20%
Inductance Test Frequency	1MHz
Rated current (Isat) (Based on Inductance change)	700mA
Rated current (Itemp)	700mA(Ambient temp.105°C)
(Based on Temperature rise)	500mA(Ambient temp.125°C)
Max. of DC resistance	0.18Ω
Class of magnetic shield	Shielded (Ferrite Core)
Self resonance frequency (min.)	30MHz
Brand	Murata
Operating Temperature Range	-40°C to 125°C
Series	LQW43FT_0H

3 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LQW43FT220M0H# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=LQW43FT220M0H%2

"#"at the end indicates the package specification code.




Notice For General

In operating temperatures exceeding +105°C, derating of current is necessary for this series.

Please apply the derating curve shown in the chart according to the operating temperature.

Derating of Rated Current



4 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.



information provided may not be the most current.

Please download the latest datasheet of LQW43FT220M0H# from the official website of Murata

La Company Com

http://www.murata.com/en/products/productdetail?partno=LQW43FT220M0H%2

LQW43FT220M0H#


"#"at the end indicates the package specification code.


Note: If you have not downloaded this document from our official website, please note that the




Characteristic Data

The charts below may show another part number which shares its characteristics.







LQW43FT220MOH |Z|

5 of 5

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

