

ATGBICS ABCU-5740RZ Avago Broadcom Compatible Transceiver
SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: ABCU-5740RZ-C

Product name : ABCU-5740RZ Avago Broadcom
Compatible Transceiver SFP 10/100/1000Base-T (RJ45,
Copper, 100m)



ABCU-5740RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS ABCU-5740RZ Avago Broadcom Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS ABCU-5740RZ SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Our Avago compatible ABCU-5740RZ SFP module supports 10/100/1000 auto negotiation and auto MDI/MDIX. It can withstand rugged environments with operating temperatures of between -40 to +85°C. Our product is built to meet or exceed the specification of Avago ABCU-5740RZ= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Certificates	
SFP transceiver type *	Copper	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Maximum data transfer rate *	1000 Mbit/s	Compliance certificates	RoHS
Interface type *	SFP	Certification	CE, FCC, RoHS
Single-mode fiber (SMF) supported	✗	Sustainability	
Multi-mode fiber (MMF) supported	✗	Sustainability compliance	✓
SFP transceiver standard	TX	Doesn't contain	Lead
Maximum transfer distance	100 m	Operational conditions	
Ethernet LAN	✓	Minimum operating temperature	-40 °C
Ethernet interface type	Gigabit Ethernet	Maximum operating temperature	85 °C
Networking standards	IEEE 802.3bq	Operating temperature (T-T)	-40 - 85 °C
Copper ethernet cabling technology	10BASE, 100BASE, 1000BASE	Storage temperature (T-T)	-40 - 85 °C
Auto MDI/MDI-X	✓	Operating relative humidity (H-H)	5 - 85%
Digital Diagnostics Monitoring (DDM)	✗	Storage relative humidity (H-H)	5 - 85%
Features		Weight & dimensions	
Product colour	Silver	Width	13.4 mm
Housing material	Metal	Depth	56.5 mm
Plug and Play	✓	Height	8.5 mm
Hot-Plug support	✓	Weight	20 g
Hot-swap	✓	Packaging content	
Easy to install	✓	Quantity per pack	1 pc(s)
Brand compatibility	Avago Technologies	Packaging data	
Power		Package type	Box
Input voltage	3.3 V	Logistics data	
Maximum voltage	4 V	Country of origin	China
Power consumption (typical)	1.3 W		



5056468750440

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-OCT-2024. Prints or copies of Information are only valid on the printed Publication date