

Bus system cable - SAC-4P-M12MS/ 3,0-980/SDA - 1557235

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Bus system cable, PROFINET, 4-pos., PUR green, shielded, straight M12 plug D-coded to USB type A/ standard, length: 3 m, customer variant



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 046356 287876
GTIN	4046356287876

Technical data

Dimensions

Length of cable	3 m
-----------------	-----

Ambient conditions

Degree of protection	IP67 (M12 connector)
	IP20 (USBconnector)

General

Rated current at 40°C	1 A
Rated voltage	48 V AC
	60 V DC
Number of positions	4
Signal type/category	FireWire
Degree of pollution	2
Insertion/withdrawal cycles	≥ 100

Material

Flammability rating according to UL 94	НВ
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 6.6
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	NBR

Cable



Bus system cable - SAC-4P-M12MS/ 3,0-980/SDA - 1557235

Technical data

Cable

Shielding	Tinned copper braided shield
External sheath, color	water blue RAL 5021
External cable diameter	6.70 mm
Outer sheath, material	PUR

Standards and Regulations

Flammability rating according to UL 94	НВ

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1557235