


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.30	阿树

Specifications:

规格:

- Voltage rating:30VAC/DC
额定电压: 30V AC/DC
- Current rating:0.5A AC/DC
额定电流: 0.5A AC/DC
- Withstanding voltage:500V AC/minute
耐受电压: 500V AC/分钟
- Temperature range: -30℃-+70℃
温度范围: -30℃-+70℃
- Insulation resistance:≥100MΩ
绝缘电阻: ≥100MΩ
- Contact resistance:≤30mΩ
接触电阻: ≤30mΩ

SCHEMATIC	
Model	DC-011A
Center Pin	Ø0.65 mm

5	Housing	1	H62 Brass rods T=0.30	Nickel plating
4	Spring	1	H62 Phosphor copper strip T=0.25	Ag plating
3	Inserts	1	H62 Brass rods T=0.30	Ag plating
2	Center Pin	1	Brass wire	Copper tin plating
1	Pedestal	1	PPA	Black
NO	NAME	QTY	MATERIAL	Remark

DESIGN	阿树	VIEW:		MODEL TYPE:	DC POWER JACK
CHECKED		UNIT:	mm/in	PART NO.:	DC-011A
APPROVED		SIZE:	A4	DWG NO.:	

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



XKB INDUSTRIAL PRECISION CO.,LIMITED

SCALE	PAGE	REVISION
N/A	1/1	A1

