MAPX	MODIFICATION	DATE





TOLERANCE: ±0.05,
RECOMMENDED PCB LAYOUT
(TOP VIEW)

NOTES:

1.MATERIAL:
- 1.1 HOUSING: HIGIH TEMPERATURATURE THERAL PLASTIC.
- 1.2 SPRING CONTACT: COPPER ALLOY.
- 1.3 FLAT CONTACT;COPPER ALLOY
- 1.4 SHELL :COPPER ALLOY.
- 1.5 COVER:HIGIH TEMPERATURATURE THERAL PLASTIC.

2.FINISH:
- 2.1 CONTACT: (SEE P/N.),[50μ"] MIN. NICKEL UNDERPLATING OVER ALL.
- 2.2 SHELL: [50μ"] MIN.SOLDERABLITY NICKEL UNDERPLATING OVER ALL.







PIN NO.	PIN 1	PIN 2	PIN 3	PIN 4
SLGNAL NAME	V BUS	D−	D+	GND
REMARK	USB 2.0 CONTACT PINS			

PIN NO.	PIN 5	PIN 6	PIN 7	PIN 8	PIN 9
SLGNAL NAME	STDA_SSRX−	STDA_SSRX+	GND_DRAIN	STDA_SSTX−	STDA_SSTX+
REMARK	USB 3.0 CONTACT PINS				

产品图
PRODUCT CHART DWG

公差一览表
TOLERANCE UNLESS OTHERMSE

X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	尹先华	制图料号 PRODUCT PART NO.	916-152A2058Y20201		
比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	AF3.0 180度15.0直脚无边铜壳LCP蓝色		
日期 DATE	2021-04-14	核准 APPD	黄国荣	角法 VIEW		版本 VER	A0