




MTA 100

TE Internal #: 2-644489-2

PCB Mount Header, Right Angle, Wire-to-Board, 2 Position, 2.54 mm [.1 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Signal, MTA 100

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles > PCB Header, Right Angle, Polyester, 2.54 mm



Connector System: **Wire-to-Board**

Number of Positions: **2**

Number of Rows: **1**

Centerline (Pitch): **2.54 mm [.1 in]**

PCB Mount Orientation: **Right Angle**

[All PCB Header, Right Angle, Polyester, 2.54 mm \(21\)](#)

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Connector System                  | Wire-to-Board         |
| Header Type                       | Fully Shrouded        |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type       | PCB Mount Header      |

Configuration Features

|                       |             |
|-----------------------|-------------|
| Number of Positions   | 2           |
| Number of Rows        | 1           |
| PCB Mount Orientation | Right Angle |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 250 VAC |
|-------------------|---------|

Body Features

|  |  |
|--|--|
|  |  |
|--|--|



|                       |       |
|-----------------------|-------|
| Primary Product Color | Black |
|-----------------------|-------|

Contact Features

|                                                         |                 |
|---------------------------------------------------------|-----------------|
| Contact Mating Area Length                              | 5.1 mm[.2 in]   |
| Mating Square Post Dimension                            | .64 mm[.025 in] |
| PCB Contact Termination Area Plating Material Thickness | .76 µm[30 µin]  |
| Contact Layout                                          | Inline          |
| Contact Underplating Material Thickness                 | 1.27 µm[50 µin] |
| Contact Mating Area Plating Material Thickness          | .76 µm[30 µin]  |
| Contact Shape & Form                                    | Square          |
| Contact Mating Area Plating Material Finish             | Bright          |
| Contact Underplating Material                           | Nickel          |
| PCB Contact Termination Area Plating Material           | Gold            |
| Contact Base Material                                   | Copper Alloy    |
| Contact Mating Area Plating Material                    | Gold            |
| Contact Type                                            | Pin             |
| Contact Current Rating (Max)                            | 5 A             |

Termination Features

|                                          |                       |
|------------------------------------------|-----------------------|
| Square Termination Post & Tail Dimension | .64 mm[.025 in]       |
| Termination Post & Tail Length           | 3.3 mm[.13 in]        |
| Termination Method to PCB                | Through Hole - Solder |

Mechanical Attachment

|                         |               |
|-------------------------|---------------|
| Mating Alignment Type   | Polarization  |
| Mating Retention        | With          |
| Panel Mount Feature     | Without       |
| Mating Retention Type   | Friction Lock |
| Connector Mounting Type | Board Mount   |
| Mating Alignment        | With          |
| PCB Mount Alignment     | Without       |
| PCB Mount Retention     | Without       |

Housing Features

|                          |                |
|--------------------------|----------------|
| Right Angle Bending Side | Front          |
| Housing Material         | Polyester - GF |
| Centerline (Pitch)       | 2.54 mm[.1 in] |



Dimensions

|                             |                  |
|-----------------------------|------------------|
| Connector Length            | 9.75 mm[.384 in] |
| Connector Height            | 10.41 mm[.41 in] |
| PCB Thickness (Recommended) | 1.6 mm[.063 in]  |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |        |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

Industry Standards

|                                             |                       |
|---------------------------------------------|-----------------------|
| Compatible With Agency/Standards Products   | CSA, UL               |
| Compatible With Approved Standards Products | CSA LR7189, UL E28476 |
| UL Flammability Rating                      | UL 94V-0              |

Packaging Features

|                    |          |
|--------------------|----------|
| Packaging Quantity | 1000     |
| Packaging Method   | Bag, Box |

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Wave solder capable to 240°C                                                                                                    |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part





numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # CAT-104MTA-NGPMR  
Nylon Gold Plated Receptacle: 2.54 mm, with Mating Alignment, MTA 100




TE Part # CAT-104MTA-NGPNR  
Nylon Gold Plated Receptacle: 2.54 mm, no Mating Alignment



TE Part # 640550-2  
02P MTA100 COVER



TE Part # CAT-104MTA-NYLCC  
Nylon PCB Connector Covers: 2.54 mm, MTA 100



TE Part # 3-644343-2  
02P MTA100 CONN ASSY ON TAPE

Also in the Series | MTA 100



Connector Caps & Covers(69)




Connector Contacts(8)



Connector Hardware(1)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(441)



Standard Rectangular Connectors(495)



Wire-to-Board Connector Assemblies & Housings(1)

Customers Also Bought



TE Part #5102154-4  
A/L UNIV HDR 20P VERT

TE Part #7-215083-6  
MICRO-MATCH MOW.06P

TE Part #9-6437287-9  
SUPER SEAL 26POS CAP ASSY H AU

TE Part #1462038-4  
IM01CGR=IM RELAY 140mW 3V HDV

TE Part #5-103908-3  
04 MTE HDR SRST LATCH W/HLDWN

TE Part #5-103908-1  
02 MTE HDR SRST LATCH W/HLDWN

TE Part #5-103908-2  
03 MTE HDR SRST LATCH W/HLDWN

TE Part #2-1623708-3  
RGP0207CH 5% 130M

TE Part #10206735-00  
PRESS,XDCR,5525DSO-DB002DS

TE Part #2333210-3  
1POS,FAKRA AUT,HDR ASSY,180DEG, COD C

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2-644489-2\_K.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-644489-2\_K.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-644489-2\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals



CSA Certificate

English

CSA Certificate

English