
Item no.:	735-306
Product description:	PCB TERMINAL BLOCK 2 SOLDER PINS / 6 POLE WITH PUSH BUTTONS PIN SPACING 5 MM / 0.197 IN WITHOUT SPACER LOW VERSION WITH TEST SLOT FOR TEST PLUG 1 MM Ø



Produkt kann von Bild abweichen / product may differ

Packing unit 160 pieces

RoHS compliant

Weight	4.82 g
Color	gray
No. of connection Points	6
No. of potentials	6
pole count	6
Height	15.9 mm
Height	0.626 in
Width	30 mm
Width	1.181 in
Depth	10.8 mm
Depth	0.425 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	10 A

Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	10 A
Connection method	PUSH WIRE®



Cross section [mm ²]	0.5 - 1.5 mm ²
Wiring method	solid
Cross section [AWG]	20 - 16 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
735-306	CCA	NL6288	400	17,5	0,5-1,5
735-306	CSA	18677-47	300	10	20-12
735-306	KEMA	2110204.11	400	17,5	0,5-1,5
735-306	RMR	11130002	400	10	0,08-0,5
735-306	UR	E45171	600	10	12
735-306	UR	E45172	300	10	20-16

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected