




Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: **Wire-to-Board**
Number of Positions: **2**
Number of Rows: **1**
Centerline (Pitch): **5 mm [.197 in]**
PCB Mount Orientation: **Right Angle**

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Keying & Polarized Position Locations	1C
Number of Positions	2
Number of Rows	1
PCB Mount Orientation	Right Angle

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

PCB Contact Termination Area Plating Material Thickness	3.8 µm[149.6 µin]
Contact Layout	Inline
Mating Tab Width	6.3 mm[.248 in]
Mating Tab Thickness	.8 mm[.032 in]
Contact Underplating Material Thickness	1.3 µm[51.18 µin]
Contact Mating Area Plating Material Thickness	3.8 µm[149.6 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	16 A

Termination Features

Square Termination Post & Tail Dimension	.8 mm[.032 in]
Termination Post & Tail Length	3.8 mm[.14 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Boss
Mating Alignment Type	Keyed, Polarization
Mating Retention	With
Panel Mount Feature	Without
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without

Housing Features

Housing Material	PA 6 Nylon
Centerline (Pitch)	5 mm[.197 in]

Dimensions



Connector Length	12.3 mm[.48 in]
Connector Height	14.9 mm[.58 in]
Connector Width	17.9 mm[.705 in]
PCB Thickness (Recommended)	1.5 mm[.059 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	208
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 521384-2 ASSY PL R/A RAST5 HEADER 02-A	 TE Part # 1969352-2 ASSY DIN R/A RAST5 HDR 02-A, G	 TE Part # 3-521384-2 ASSY PL R/A RAST5 HEADER 02-E	 TE Part # 1-521384-2 ASSY PL R/A RAST5 HEADER 02-B
 TE Part # 1955660-7 RAST 5,HSG,7P,RIGHT ANGLE, GWT	 TE Part # 2-521384-2 ASSY PL R/A RAST5 HEADER 02-C	 TE Part # 4-521384-2 ASSY PL R/A RAST5 HEADER 02-G	 TE Part # 5-521384-2 ASSY PL R/A RAST5 HEADER 02-I
 TE Part # 5-521385-2 ASSY DIN R/A RAST5 HEADER 02-I	 TE Part # 521386-4 ASSY PL R/A RAST5 HDR 4P SP	 TE Part # 6-521384-2 ASSY PL R/A RAST5 HEADER 2P	 TE Part # 2178618-3 ASSY DIN R/A RAST5 HEADER 03-A

Also in the Series | RAST 5 IDC Connectors


 Automotive Terminals(8)	 Connector Contacts(14)	 Crimp Terminal Housings(39)	 Insertion & Extraction Tools(1)
--	--	--	--



PCB Headers & Receptacles(417)



Rectangular Connector Housings(1)



Standard Edge Connectors(32)




Standard Rectangular Connectors(63)



Wire-to-Board Connector Assemblies
& Housings(202)

Customers Also Bought




TE Part #1586042-4
4P VAL-U-LOK R/A HDR V0



TE Part #643960-1
03P MTA156 HDR ASSY STR W/O#2




TE Part #1-480705-0
06P UMNL CAP HSG NATL




TE Part #63849-1
250 FASTON TAB TPBR



TE Part #696153-2
TERM, WIRE PIN, PIDG, 22-16, T&R




TE Part #1217754-1
250 FASTON,FLAG,PCB TAB,TNBR



TE Part #3-647609-5
05P MTA100 HDR ASSY F/L LF



TE Part #1601097-3
TAB,2.79X0.81,STD,SMZ



TE Part #1721923-6
OJE-SS-112HMF,000T0



TE Part #1969498-1
ASSY, TAB HDR, 7MM, 6.35 SERIES, 2 POS

Documents



Product Drawings

ASSY DIN R/A RAST5 HDR 02-A, G

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-1969352-2_A_c-5-1969352-2-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-1969352-2_A_c-5-1969352-2-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1969352-2_A_c-5-1969352-2-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

RAST Connector System Catalog

English

Product Specifications

Product Specification

English

Agency Approvals

UL Report

English