



Features

- Bi-directional ESD protection of one line
- Reverse stand-off voltage: 12V/36V
- Low reverse clamping voltage
- Low leakage current
- Fast response time
- IEC 61000-4-2 (ESD) immunity test :
- Air discharge: $\pm 30\text{kV}$
- Contact discharge: $\pm 30\text{kV}$



Marking Diagram

ADM



SOT-23 mechanical data

UNIT	A	C	D	E	He	e	M	L	L ₁	a
mm	max	1.1	0.15	1.4	3.0	2.6	0.5	1.95	0.55 (ref)	0.36 (ref)
	min	0.9	0.08	1.2	2.8	2.2	0.3	1.7		
mil	max	43	6	55	118	102	20	77	22 (ref)	14 (ref)
	min	35	3	47	110	87	12	67		

Description

Designed to protect voltage sensitive electronic components from ESD and other transients. Excellent clamping capability, low leakage, low capacitance, and fast response time provide best in class protection on designs that are exposed to ESD.

The combination of small size, low capacitance, and high level of ESD protection makes them a flexible solution for applications such as HDMI, Display Port TM, and MDDI interfaces. It is designed to replace multiplayer varistors (MLV) in consumer equipments applications such as mobile phone, notebook, PAD, STB, LCD TV etc.

Applications

- Computers and peripherals
- High speed data lines
- Audio and video equipment
- Cellular handsets and accessories
- Subscriber identity module(SIM) card protection
- Portable electronics
- FireWire
- Other electronics equipments communication systems

ES1236D2HA23

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (PIN1/PIN2 to PIN3)	Ppk	360	W
Peak Pulse Power (PIN3 to PIN1/PIN2)	Ppk	360	W
Peak Pulse Current (PIN1/PIN2 to PIN3)	IPP	4	A
Peak Pulse Current (PIN3 to PIN1/PIN2)	IPP	15	A
ESD per IEC 61000-4-2 (Air)	VESD	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Operating Temperature Range	TJ	-55 to +125	°C
Storage Temperature Range	Tstg	-55 to +150	°C

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	VR _{WM}	PIN1/PIN2 to PIN3			36	V
		PIN3 to PIN1/PIN2			12	V
Breakdown Voltage	VBR	IT=1mA, tp=8/20μs, PIN1/PIN2 to PIN3	39.5		45	V
		IT=1mA, tp=8/20μs, PIN3 to PIN1/PIN2	14.2		16.2	V
Reverse Leakage Current	IR	VR _{WM} = 36V, PIN1/PIN2 to PIN3			0.2	uA
		VR _{WM} = 12V, PIN3 to PIN1/PIN2			0.2	uA
Clamping Voltage	Vc	I _{PP} = 4A (8 x 20μs pulse), PIN1/PIN2 to PIN3			60	V
		I _{PP} = 15A (8 x 20μs pulse), PIN3 to PIN1/PIN2			24	V
Junction Capacitance	C _j	VR = 0V, f = 1MHz			50	pF

Electronics Parameter


Symbol	Parameter
I _T	Test Current
I _{PP}	Maximum Reverse Peak Pulse Current
V _c	Clamping Voltage @ I _c
V _{BR}	Breakdown Voltage @ I _T
I _R	Reverse Leakage Current @ VR _{WM}
V _{RW}	Reverse Standoff Voltage




Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



ESD pulse waveform according to IEC61000-4-2



Power Derating Curve



8/20μs pulse waveform according to IEC 61000-4-5