





*Quality Products. Service Excellence.*

## Type 12 Mild Steel Pushbutton Enclosures 1489 Series

### Hinged Cover



### Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

### Standards

- UL 508A Type 12
- CSA Type 12
- **Complies with**
  - NEMA Type 12
  - IEC 60529, IP54
- Appropriate components are required to maintain these standards.

### Construction

- Formed 14 gauge steel.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Continuously hinged cover is secured with captive, plated steel screws which fasten into threaded sealed wells.
- Oil resistant gasket and adhesive.
- Weldnuts are provided for mounting inner panels.
- A removable 14 gauge inner panel is included.
- A bonding stud is provided on the door and a grounding stud is provided in the enclosure

### Finish

- Cover and enclosure are phosphatized and finished in ANSI 61 gray powder coating.
- Removable inner panel is finished in white powder coating.

### Accessories

- Hole Plugs
- Pedestal and Base
- General Accessories

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

| 30.5mm PB | 22.5mm PB | No. Of | Enclosure |      |      | Panel |      |
|-----------|-----------|--------|-----------|------|------|-------|------|
| Part No.  | Part No.  | Holes  | H         | W    | D    | H     | W    |
| 1489P4    | 1489MP4   | 4      | 8.25      | 7.25 | 6.00 | 6.25  | 5.25 |

| 30.5mm PB | 22.5mm PB | No. Of | Enclosure |       |      | Panel |       |
|-----------|-----------|--------|-----------|-------|------|-------|-------|
| Part No.  | Part No.  | Holes  | H         | W     | D    | H     | W     |
| 1489P6    | 1489MP6   | 6      | 10.50     | 7.25  | 6.00 | 8.50  | 5.25  |
| 1489P9    | 1489MP9   | 9      | 10.50     | 9.50  | 6.00 | 8.50  | 7.50  |
| 1489P12   | 1489MP12  | 12     | 12.75     | 9.50  | 6.00 | 10.75 | 7.50  |
| 1489P16   | 1489MP16  | 16     | 12.75     | 11.75 | 6.00 | 10.75 | 9.75  |
| 1489P20   | 1489MP20  | 20     | 15.00     | 11.75 | 6.00 | 13.00 | 9.75  |
| 1489P25   | 1489MP25  | 25     | 15.00     | 14.00 | 6.00 | 13.00 | 12.00 |
| 1489P30   | 1489MP30  | 30     | 17.25     | 14.00 | 6.00 | 15.25 | 12.00 |
| 1489P36   | 1489MP36  | 36     | 17.25     | 16.25 | 6.00 | 15.25 | 14.25 |
| 1489P42   | 1489MP42  | 42     | 19.50     | 16.25 | 6.00 | 17.50 | 14.25 |

*Data subject to change without notice*

© 2019. Hammond Manufacturing Ltd. All rights reserved.