

DASH NO.	DESCRIPTION	MADE FROM	REVISIONS										
KM-59-14		NOTES: 1. FOR USE WITH RG-180/U CABLE. 2. MATERIALS: BRASS QQ-B-62G, TEFLON MIL-P-19468, CRESSKILL COMPOUND SR 837A-70, BUNAN DUROMETER 50-60. 3. PLATING: HARD GOLD PLT. OVER NICKEL PLT. 4. ELECTRICAL CHARACTERISTICS: PEAK VOLTAGE: 500 V. NOMINAL IMPEDANCE: 50 Ω UNMATCHED FREQUENCY: UP TO 500 MC.	<table border="1"> <thead> <tr> <th>ISSUE</th> <th>CHANGES</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>ER 4652 16 DEC 66 J.G.</td> </tr> <tr> <td>1</td> <td>CN 4945 AT 27 APR 67</td> </tr> <tr> <td>2</td> <td>CN 8155A L.R. 31 JAN 70</td> </tr> <tr> <td>3</td> <td>CN 10491A WLA 20 NOV 71</td> </tr> </tbody> </table>	ISSUE	CHANGES	0	ER 4652 16 DEC 66 J.G.	1	CN 4945 AT 27 APR 67	2	CN 8155A L.R. 31 JAN 70	3	CN 10491A WLA 20 NOV 71
			ISSUE	CHANGES									
			0	ER 4652 16 DEC 66 J.G.									
			1	CN 4945 AT 27 APR 67									
2	CN 8155A L.R. 31 JAN 70												
3	CN 10491A WLA 20 NOV 71												
<table border="1"> <thead> <tr> <th>USED ON:</th> </tr> </thead> <tbody> <tr> <td>REF: LIQUIDOMETER 562 PL 1 REV. E</td> </tr> <tr> <td>FINISH:</td> </tr> <tr> <td>SPEC:</td> </tr> <tr> <td>MATL:</td> </tr> <tr> <td>SPEC:</td> </tr> </tbody> </table>	USED ON:	REF: LIQUIDOMETER 562 PL 1 REV. E	FINISH:	SPEC:	MATL:	SPEC:							
USED ON:													
REF: LIQUIDOMETER 562 PL 1 REV. E													
FINISH:													
SPEC:													
MATL:													
SPEC:													
<table border="1"> <thead> <tr> <th colspan="2">PLUG (POLARIZED)</th> </tr> </thead> <tbody> <tr> <td>DRAWN MJB</td> <td>DATE 29 MAY 76</td> </tr> <tr> <td>APPR J</td> <td>DATE 31 MAY 76</td> </tr> </tbody> </table>	PLUG (POLARIZED)		DRAWN MJB	DATE 29 MAY 76	APPR J	DATE 31 MAY 76							
PLUG (POLARIZED)													
DRAWN MJB	DATE 29 MAY 76												
APPR J	DATE 31 MAY 76												
KINGS ELECTRONICS 40 MARLBOROUGH ROAD TUCKAHOE, N. Y. 10707													
KM-59-14													

SD

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS $\pm .010$
2. REMOVE ALL BURRS. BREAK SHARP EDGES .005 MAX.
3. 3 PLACE DECIMALS $\pm .004$
3. ANGLES $\pm 0^\circ 30'$
3. NO FILLETS PERMITTED.
1. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED HALF THE SUM OF THEIR TOLERANCES.
4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.