

> 800/4 Z Bits

**Anwendung:**

Schlitzschrauben

Antrieb:1/4"-Sechskant, passend für Halter nach
DIN 3126-F 6,3, ISO 1173**Ausführung:**Zähhart, besonders geeignet für den harten
Schraubfall z. B. in Blech oder Metall

Code



mm



mm



mm



mm



mm



05059305001

0,5

3,0

50

2"

3,0

10



05059466001

0,5

3,0

70

2 3/4"

3,0

10



05059307001

0,5

4,0

50

2"

4,0

10



05059310001

0,6

3,5

50

2"

3,5

10



05059472001

0,6

3,5

70

2 3/4"

3,5

10



05059450001

0,6


3,5

152

6"

3,5

10



05059315001

0,6

4,5

50

2"

4,5

10



05059489001

0,6

4,5

89

3 1/2"

4,5

10



05059320001

0,8

4,0

50

2"

4,0

10



05059478001

0,8

4,0

70

2 3/4"

4,0

10



05059480001

0,8

4,0

89

3 1/2"

4,0

10



05059451001

0,8

4,0

152

6"

4,0

10



05059325001

0,8

5,5

50

2"

5,5

10



05059330001

1,0

5,5

50

2"

5,5

10



05059486001

1,0

5,5

70

2 3/4"

5,5

10



05059488001

1,0

5,5

89

3 1/2"

5,5

10



05059452001

1,0

5,5

152

6"

5,5

10



05059335001

1,0

6,0

50

2"

6,0

10



05059337001

1,2

6,5

50

2"

6,2

10



05059492001

1,2


6,5

70

2 3/4"

6,2

10



05059490001

1,2

6,5

89

3 1/2"

6,2

10



05059453001

1,2

6,5

152

6"

6,2

10



05059340001

1,2

8,0

50

2"

8,0

10



05059496001

1,2

8,0

89

3 1/2"

8,0

10



05059345001

1,6

8,0

50

2"

8,0

10



05059500001

1,6

8,0

89

3 1/2"

8,0

10

