



Amphenol Sine Systems, **USA**
Amphenol Tuchel Industrial, **Germany**
Amphenol Audio, **USA**

OUR PRODUCT LINES | MARKET APPLICATIONS | DISTRIBUTORS | HOME | NEWS & EVENTS | CONTACT US

Select Language | Select Language

PRODUCT SELECTOR

PRODUCT TYPE	POSITIONS	IP RATING	AMPERAGE	HOUSING MATERIAL	PRODUCT LINE
<div>Search All</div>	<div>Search All</div>	<div>Search All</div>	<div>Search All</div>	<div>Search All</div>	<div>Search All</div>

VOLTAGE

Search All

RESET

SEARCH

Home > Our Product Lines > C091 Connectors > C091 A > 12 Position Cable Connectors > T3636552 Female straight cable connector with internal strain relief and metal locking ring. 12 contacts, 6-8mm cable diameter.



T3636552 FEMALE STRAIGHT CABLE CONNECTOR WITH INTERNAL STRAIN RELIEF AND METAL LOCKING RING. 12 CONTACTS, 6-8MM CABLE DIAMETER.

PART NUMBER: T3636552

DATASHEET: View / Download

SPECIFICATIONS:

- Contacts: 12
- Cable Diameter: 6 - 8mm
- Current Rating: 3A
- Termination: Crimp
- Locking: Screw
- Insert: Thermoplastic
- Version: Straight
- Wire Gauge: 0.09 - 0.25mm² (28-24 AWG)
- Housing: Zinc die cast, nickel plated
- Protection: IP40
- Insertion/Withdrawal Force: 50 N
- Insulation Resistance: > 10(10) Ω
- Rated Voltage IEC 60664-1: 150V
- Rated Voltage per UL 1977: 60V
- Rated Impulse Withstanding Voltage IEC 60664-1: 1200V
- Contact Resistance: <5 m ohms
- Operating Temperature: -40°C to +100°C
- Mating Part(s): T3635552,T3637550,T3637150

QUANTITY

1

REQUEST A QUOTE

Like Sign Up to see what your friends like.

Like Sign Up to see what your friends like.

Female straight cable connector with internal strain relief and metal locking ring. 12 contacts, 6-8mm cable diameter. Screw locking according to DIN EN 60130-9 / IEC 60130-9. Contacts sold separately.

RELATED ITEMS



T3635552 Male straight cable connector with internal strain relief and metal locking ring. 12 contacts, 6-8mm cable diameter



T3636552 Female straight cable connector with internal strain relief and metal locking ring. 12 contacts, 6-8mm cable diameter.



T3637550 Front mounting male receptacle with ring nut. 12 contacts



T3637150 Rear mounting male receptacle with ring nut. 12 contacts.



T3638550 Front mounting female receptacle with ring nut. 12 contacts



T3638150 Rear mounting female receptacle with ring nut. 12 contacts

BROWSE SIMILAR ITEMS

- > Market Applications > Heavy Equipment > Agriculture > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Heavy Equipment > Construction > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Heavy Equipment > Transportation > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Heavy Equipment > Off Road Recreation > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Heavy Equipment > Industrial > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Automation > Conveyors > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Automation > Packaging Machinery > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Automation > Motion Control / Servo Motors > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Medical > C091 Connectors > C091 A > 12 Position Cable Connectors
- > Market Applications > Wireless Infrastructure > C091 Connectors > C091 A > 12 Position Cable Connectors

[LINKS](#)

[SHOP](#)

[FOLLOW US!](#)

- > Company
- > Contact
- > Privacy
- > Terms and Conditions
- > Code of Business Conduct and Ethics
- > ISO Certification
- > Quality Policy
- > Industrial@Amphenol News
- > Test Reports
- > Our Product Lines
- > Market Applications
- > Distributors

