








Product Type Features	
Contactor Type	Sealed
Terminal Configuration	8-32 UNC-2A Stud
Mechanical Attachment	
Mounting Plate	With
Electrical Characteristics	
Actuating System 	DC
Contact Rating	400A
Coil - Rated Voltage (VDC) 	24 - 30
Coil Voltage, Max. (VDC) 	30
Contact - Limiting Continuous Current-obs	Intermittent
Termination Features	
Auxiliary Contact Terminals	10-32 UNF-2A Stud
Coil Termination	10-32 UNF-2A Stud

Body Features	
Torque	112 In-lbs
Arc Cover	Without
Mount Type	Chassis
Contact Features	
Number of Poles 	1
Configuration Features	
Contact - Arrangement 	SPST-
Auxiliary Switch Contact Arrangement	SPDT,
Industry Standards	
RoHS/ELV Compliance 	Not EL
Lead Free Solder Processes 	Not re proces
Other	
Series	A Seri
Brand	Hartm

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[Global Accessibility Statement](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)