



方成电子（东莞）有限公司

Fang cheng Electronics(Dong guan) Co,LTD

SPECIFICATION FOR APPROVAL

CUSTOMER:

Part Number : 大电流功率电感

CUSTOMER Number:

CUSTOMER Part : HIGH CURRENT POWER INDUCTOR

Fangcheng part : FC-DL22D-200MT

DATE: 2025-9-03

REV: 01

RoHS
COMPLIANT

Confidential

made in fangcheng:

CUSTOMER APPROD:

prepad	checd	Approd
黄敏	罗佳	<u>Jason Yuan</u>

prepad	checd	Approd

THE INFORMATION CONTAINED IN THIS DOCUMENT IS OF A PROPRIETARY NATURE AND IS INTENDED TO BE KEPT CONFIDENTIAL BETWEEN THE SENDER AND THE INTENDED RECIPIENT. IT MAY NOT BE REPRODUCED OR USED WITHOUT EXPRESS WRITTEN PERMISSION OF FC TECHNOLOGIES, OR FC

Fangcheng Electronics (Dongguan) Co., Ltd.

Tel: +86 0769-82988010

Fax: +86 0769-82988065

E-mail: yhl@fangchengcoils.com

URL: www.fangchengcoils.com

Address: Building 3, Jinmei Technology Park, No.16 Huanchang West Road, Changping Town, Dongguan City

Fangcheng Electronics (China-Taiwan)

Address: No. 31, MRT Road, Zhonghe District, New Taipei City

Tel: +8869-983491379

Postcode: 235050



Description of Revision

REV	Description of Revision	DATE	Prepad	Notes
01	Initial Release	2025. 9. 3	黄敏	

Customer:

made : 方成电子（东莞）有限公司

Part Number: FC-DL22D-200MT

Page: 3 ----- 8

Notice of Use

For the parameters not prescribed in the *Specification for Approval*, please refer to the following standards or the relative industry standards.

1. Product in packing storage condition : temperature 540, RH70%.

2. A storage of - F C -Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.

3. Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.

4 Always handle products with care.

5 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.

Always ensure optimum conditions for soldering.

6 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.

7 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.

8 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.

IPC 020D Joint Industry standard

IEC1007 《Transformer and inductors for use in electronic and telecommunication equipment—Measuring methods and test procedures》

(ROHS or other environmental request)



中国认可
国际互认
CNAS CO28-M



环境管理体系认证证书-编号:02825E11713R0S

质量管理体系认证证书-编号:02825Q12617R0S

Prepad

黄敏


Checd

罗佳


Approd

Jason Yuan

1. Appearance and Dimensions(mm)





2. Schematic :



General Properties:

It is recommended that the temperature of the component does not exceed +125°C under worst case conditions	
Storage Temperature (in original packaging)	-20 °C up to +60 °C
Operating Temperature	-40 °C up to +125 °C
Temperature Rise < 55K	
Test conditions of Electrical Properties: +20°C, 33% RH if not specified differently	

3. PCB LAYOUT:(mm)




Prepad 黄敏	Checd 罗佳	Approd Jason Yuan
--------------	-------------	----------------------

4. Electrical Characteristics：

NO 序号	PARAMETER 参数	TERMINAL 脚位	SPCIFICATION 规格	TEST INSTRUMENTS 测试设备
1	INDUCTANCE 电感量	L=(S—F)	20. 0uH±20%	100KHz,0.3V WK3260 CHROMA 3250 or EQUAL
2	工作电流	I=(S—F)	DC=60A/max,60A Typ	WK3260B
	磁饱和电流	I=(S—F)	DC=60A/MAX/55.0ATyp	WK3260B
3	工作频率	L=(S—F)	1.0MHZ/Min	6632
4	DCR	R=(S—F)	2.0typ/3.0m Ω Max	GKT2511 25°C
5	高压测试	绕组-磁芯	DC/500 V	CH7350
6	绝缘阻抗	绕组-磁芯	100M Ω 500VDC	CH7350

Low Primary DCR version
Ambient temperature -40° C to +85° C
Storage temperature Component: -40° C to +125° C

5. @Inductance VS.DC Current Curve.




Customer:

made : 方成电子（东莞）有限公司


Part Number: FC-DL22D-200MT

Page: 6 ----- 8

6. Percent Initial Permeability VS AC Flux Density



6.2 Percent Initial Permerbility (%uo) VS DC Magnetizing Force



Prepad

黄敏

Checd

罗佳

Approd

Jason Yuan

7. Reliability and test condition:


Test item	test condition	Remark
Cold Operating Test	GB2423.1 Ad	
Heat Operating Test	GB2423.2 Bd	
Cold Storage Test	GB2423.1 Ab	
Heat Storage Test	GB2423.2 Bb	
Steady Damp Heat Test	GB2423.3 Cb	
Circular Damp Heat Test	GB2423.4 Db	
Temperature Cycling Test	GB2423.22 Nb	
Temperature Shock Test	GB2423.22 Na	
Vibration Test	GB2423.10~15 Fc, Fdb	
Mechanical Shock Test(Bump)	GB2423.5 Eb	
Free Fall Test	GB2423.8 Ed	
Solderability	GJB360A-96	
High Temperature Step Stress Test	Enhancement Test Specifications	
Low Temperature Step Stress Test		
High-speed Thermal Cycling		
Limit Vibration		
Composite Stress		
Highly-Accelerated Temperature and Humidity Stress Test(HAST) (		



Prepad 黄敏	Checd 罗佳	Approd Jason Yuan
--------------	-------------	-----------------------------

8. Soldering Specification:

8.1 Reflow Profile for Components.



8.2 波峰焊温度:255℃±5℃;时间:不少于 7 秒.

波峰焊预热温度:100 至 160℃;时间:不少于 10 秒.

8.3 高温耐热性:

在 260℃ 的熔融钎料中，停留时间不少于 10 秒，无质量问题。

8.4 返修温度和时间:

温度：350℃；时间：不少于 5 秒。

8.5 焊接次数:

元器件能承受的焊接次数不少于 5 次。



9.1 包装:

- 1)包装箱上应标明产品型号、名称、数量、出厂日期、承制方名称及出厂检验章；
- 2)货物运达客户方后，包装箱封条应完好，箱体无破损、开裂等现象；
- 3)电感用木箱或其他材料包装，方便拆卸，四周用软性材料填充；

9.2 外观:

- 1)产品应有合格证和耐擦防水洗标签，应注明型号、规格；
- 2)产品外观整洁，应无破损、划伤；

9.3 检验:

- 1)产品生产中必须全数进行电气性能，抗电强度检测；箱内应有 100%电气性能合格保证书或检测报告；
- 2)产品出货前按批次，必须根据承认书按国家行业标准进行抽样检验，合格后出具出厂检验报告，记录抽样测试数据，

Prepad 黄敏	Checd 罗佳	Approd Jason Yuan
--------------	-------------	----------------------