

14GUG32AF | US2:14GUG32AF



Non-reversing motor starter Size 2 1/2 Three phase full voltage Solid-state overload relay OLRelay amp range 25-100A 110VAC 50HZ / 120VAC 60HZ coil Combination type No enclosure

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Image similar
> Image gallery and data for M-CAD and E-CAD (3) (3)

Product data Further Product Information

Product	
Article Number (Market Facing Number)	14GUG32AF US2:14GUG32AF
Product Description	Non-reversing motor starter Size 2 1/2 Three phase full voltage Solid-state overload relay OLRelay amp range 25-100A 110VAC 50HZ / 120VAC 60HZ coil Combination type No enclosure
Product family	Ordering Data Overview
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group	UUX
List Price	Show prices
Customer Price	Show prices
Metal Factor	None
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Standard lead time ex-works	1 Day/Days
Net Weight (lb)	5.269 lb
Product Dimensions (W x L x H)	Not available
Packaging Dimension	Not available
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	Not available
UPC	783087948037
Commodity Code	8536504000
LKZ_FDB/ CatalogID	CC-IC10
Product Group	5432
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	not available
Returnable	Yes
WEEE (2012/19/EU) Take-Back Obligation	No

REACH Art. 33 Duty to inform according to the current list of candidates Reach Information

Classifications			
	Version	Classification	
eClass	6	27-37-09-05	
eClass	7.1	27-37-09-05	
eClass	8	27-37-09-05	
eClass	9	27-37-09-05	
eClass	9.1	27-37-09-05	
ETIM	5	EC001037	
ETIM	6	EC001037	
ETIM	7	EC001037	
IDEA	4	4734	
UNSPSC	15	39-12-15-21	

Buy product

Quantity 1 1 Piece

Add to cart

Frequently bought together:



> 49AB11 | US2:49AB11

49AB11 aux contact NO/NC INNOVA



> 3LD25040TK53 |

3LD25040TK53

SETRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 63 A, operating power / at AC-23 A 400 V: 22 kW, front-mounted, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle



> 3RB30261QB0 |

3RB30261QB0

Overload relay 6...25 A Electronic For motor protection Size S0, Class 10E Contactor mounting Main circuit: Screw Auxiliary circuit: Screw Manual-Automatic-Reset



> 3RF24301AB45 |

3RF24301AB45

Solid-state contactor 3-phase 3RF2 AC 51 / 30 A / 40 °C 48-600 V / 4-30 V DC 2-phase controlled screw terminal Blocking voltage 1200 V



> 3RH21311AK60 |

3RH21311AK60

Contactor relay, 3 NO + 1 NC, 110 V AC, 50 Hz, 120 V, 60 Hz, Size S00, screw terminal