
Spec Sheet

SMD Power Inductors (NR series S type)

NRS4010T2R2MDGG



Features

- Item Summary 2.2uH±20%, 1.2A, 4.0x4.0x1.0mm
- Lifecycle Stage

Mass Production

Standard packaging quantity (minimum)
 Taping Embossed 5000pcs


■ Products characteristics table

Inductance	2.2 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	1.2 A
Saturation Current (max)	1.2 A
Temperature Rise Current (max)	1.5 A
DC Resistance (typ)	85 mΩ
DC Resistance (max)	102 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	73 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.0 mm
Dimension e	1.1 ±0.2 mm

Recommended Land Patterns



2016.01.25

SMD Power Inductors (NR series S type)

NRS4010T2R2MDGG

Dimension unit: mm unit: inch

Length: 4.0 +/- 0.2 (0.157 +/- 0.008)

Width: 4.0 +/- 0.2 (0.157 +/- 0.008)

Height: 1.0 max. (0.039 max.)



Inductance: 2.2 uH (test freq at 0.1MHz)
DC Resistance: 0.085 / 0.102 ohm (typ / max)

Saturation Current: 1,200 mA (max) Temp. rise Current: 1,500 mA (max)

> Saturation current typical : 30% reduction from initial L value. Temp rise Current typical : Temperature will rise by 40 deg C

