

Description

The SX5N04MI uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.

General Features

$V_{DS} = 40V$ $I_D = 5A$


$R_{DS(ON)} < 37m\Omega$ @ $V_{GS}=10V$

Application



Wireless charging

Boost driver

LED



SOT-23-3L



Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	40	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D@T_A=25^\circ\text{C}$	Continuous Drain Current, V_{GS} @ 10V ¹	5	A
$I_D@T_A=70^\circ\text{C}$	Continuous Drain Current, V_{GS} @ 10V ¹	3.5	A
I_{DM}	Pulsed Drain Current ²	14	A
E_{AS}	Single Pulse Avalanche Energy ³	16.2	mJ
$P_D@T_A=25^\circ\text{C}$	Total Power Dissipation ⁴	1	W
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	125	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	80	$^\circ\text{C/W}$

Electrical Characteristics (T_J=25 °C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BVDSS	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	40	44	---	V
ΔBVDSS/ΔT _J	BVDSS Temperature Coefficient	Reference to 25°C , I _D =1mA	---	0.032	---	V/°C
RDS(ON)	Static Drain-Source On-Resistance ²	V _{GS} =10V , I _D =4A	---	28	37	mΩ
		V _{GS} =4.5V , I _D =3A	---	40	50	
VGS(th)	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	1.0	1.5	2.5	V
ΔVGS(th)	VGS(th) Temperature Coefficient		---	-4.5	---	mV/°C
IDSS	Drain-Source Leakage Current	V _{DS} =32V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =32V , V _{GS} =0V , T _J =55°C	---	---	5	
IGSS	Gate-Source Leakage Current	V _{GS} =±20V , V _{DS} =0V	---	---	±100	nA
gfs	Forward Transconductance	V _{DS} =5V , I _D =4A	---	8	---	S
R _g	Gate Resistance	V _{DS} =0V , V _{GS} =0V , f=1MHz	---	2.4	4.8	Ω
Q _g	Total Gate Charge (4.5V)	V _{DS} =15V , V _{GS} =4.5V , I _D =3A	---	5	---	nC
Q _{gs}	Gate-Source Charge		---	1.54	---	
Q _{gd}	Gate-Drain Charge		---	1.84	---	
Td(on)	Turn-On Delay Time	V _{DD} =15V , V _{GS} =10V , R _G =3.3Ω I _D =1A	---	7.8	---	ns
T _r	Rise Time		---	2.1	---	
Td(off)	Turn-Off Delay Time		---	29	---	
T _f	Fall Time		---	2.1	---	
Ciss	Input Capacitance	V _{DS} =15V , V _{GS} =0V , f=1MHz	---	452	---	pF
Coss	Output Capacitance		---	51	---	
Crss	Reverse Transfer Capacitance		---	38	---	
IS	Continuous Source Current ^{1,4}	V _G =V _D =0V , Force Current	---	---	4.5	A
ISM	Pulsed Source Current ^{2,4}		---	---	14	A
VSD	Diode Forward Voltage ²	V _{GS} =0V , I _S =1A , T _J =25°C	---	---	1.2	V

Note :

- 1、The data tested by surface mounted on a 1 inch² FR-4 board with 20Z copper.
- 2、The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
- 3、The power dissipation is limited by 150°C junction temperature
- 4、The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

Typical Characteristics




Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics

Typical Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area vs. Case Temperature




Figure 10: Maximum Continuous Drain Current





Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case

Package Mechanical Data-SOT23-3L-Single



Symbol	Dimensions in Millimeters		
	MIN.	TYP.	MAX.
A	1	1.1	1.2
A1	0	0.05	0.1
B	1.8	1.9	2
B1	0.95TYP		
C	0.1	0.15	0.2
D	2.82	2.92	3.02
E	1.5	1.6	1.7
E1	2.65	2.8	2.95
L1	0.3	0.4	0.5
L2	0.3	0.45	0.6

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
TAPING	SOT23-3L		3000