

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
60V	22mΩ@10V	20A
	28mΩ@4.5V	



合肥矽普半导体

Siliup Semiconductor Technology Co., Ltd

技术 品质 服务

www.siliup.com


Feature

- Fast switching speed
- Surface mount package
- ROHS Compliant & Halogen-Free
- 100% Single Pulse avalanche energy Test

Applications


- DC-DC Converters.
- Motor Control.

Package



PDFN5X6-8L

Circuit diagram



Marking



SP60N23DNK
**

:Device Code
:Week Code

Order Information

Device	Package	Unit/Tape
SP60N23DNK	PDFN5X6-8L	5000

Absolute maximum ratings (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current (Tc=25°C)	I_D	20	A
Continuous Drain Current (Tc=100°C)	I_D	13	A
Pulse Drain Current Tested	I_{DM}	80	A
Single pulsed avalanche energy ¹	E_{AS}	56	mJ
Power Dissipation (Tc=25°C)	P_D	35	W
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	3.6	°C/W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C


Electrical characteristics (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V , ID=250uA	60	-	-	V
Drain-Source Leakage Current	IDSS	VDS=48V , VGS=0V , TJ=25℃	-	-	1	uA
Gate-Source Leakage Current	IGSS	VGS=±20V , VDS=0V	-	-	±100	nA
Gate Threshold Voltage	VGS(th)	VGS=VDS , ID =250uA	1.0	1.6	2.5	V
Static Drain-Source On-Resistance	RDS(ON)	VGS =10V, ID =20A	-	22	28	mΩ
		VGS =4.5V, ID =15A	-	28	38	
Dynamic characteristics						
Input Capacitance	Ciss	VDS=30V , VGS=0V , f=1MHz	-	1304	-	pF
Output Capacitance	Coss		-	123	-	
Reverse Transfer Capacitance	Crss		-	97	-	
Total Gate Charge	Qg	VDS=30V , VGS=10V , ID=10A	-	25.3	-	nC
Gate-Source Charge	Qgs		-	4.7	-	
Gate-Drain Charge	Qgd		-	6.1	-	
Switching Characteristics						
Turn-On Delay Time	Td(on)	VDD=30V VGS=10V , RG=3Ω, ID=2A	-	6	-	nS
Rise Time	Tr		-	6.1	-	
Turn-Off Delay Time	Td(off)		-	17	-	
Fall Time	Tf		-	3	-	
Diode Characteristics						
Diode Forward Voltage	VSD	VGS=0V , IS=1A , TJ=25℃	-	-	1.2	V
Maximum Body-Diode Continuous Current	IS		-	-	20	A
Reverse recover time	Trr	IS=10A, di/dt=100A/us, TJ=25℃	-	27	-	nS
Reverse recovery charge	Qrr		-	48	-	nC


Note:

- The EAS Test condition is $V_{DD}=30V, V_{GS}=10V, L=0.5mH, R_G=25\Omega$


Typical Characteristics




Output Characteristics




Transfer Characteristics




Capacitance Characteristics




Gate Charge




Current dissipation






Power dissipation




RDS(on) VS Drain Current



Forward characteristics of reverse diode




Maximum Transient Thermal Impedance




Safe Operation Area


PDFN5X6-8L Package Information



Top View
[顶视图]



Bottom View
[背视图]



Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254 REF.		0.010 REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	1.470	1.870	0.058	0.074
D2	0.470	0.870	0.019	0.034
E1	3.375	3.575	0.133	0.141
D3	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270 TYP.		0.050 TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°