

https://www.phoenixcontact.com/us/products/1415775



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYPORT B24 panel mounting base, with single locking latch, with plastic protective cover, with stainless steel front plate connections, 4x RJ45 CAT5e (female/female)

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

Item number	1415775
Packing unit	1 pc
Sales key	BF69
Product key	BF7EGX
GTIN	4055626805764
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Country of origin	US



https://www.phoenixcontact.com/us/products/1415775



Technical data

Product properties

Product type	Stackable housing set
Housing type	Panel mounting base
Application	Standard
Туре	B24
Protective cover	yes

Electrical properties

Rated current	max. 1.5 A DC (RJ45)
---------------	----------------------

Connection data

Tightening torque	1.5 2 Nm

Dimensions

Dimensional drawing	130 140,5 232 53
Width	53 mm
Height	30.5 mm
Length	140.5 mm

Installation dimensions

installation dimensions		
	Width of the assembly cutout	35 mm
	Length of the assembly cutout	113 mm

Material specifications

Seal material	NBR, conductive
	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material, protective cover	PA
Locking latch material	Polyamide

Connector

Contact insert design	with 4x RJ45 Cat 5E Ethernet Socket/socket, snap-in slot locking
-----------------------	--

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08



https://www.phoenixcontact.com/us/products/1415775



Ambient temperature (operation)

-40 °C ... 125 °C (Housing)

1415775

https://www.phoenixcontact.com/us/products/1415775



Drawings

Dimensional drawing Ø4,5 130 140,5 53

Dimensional drawing

Dimensional drawing 130 113 113 Ø4,5

Mounting cutout



https://www.phoenixcontact.com/us/products/1415775



Classifications

ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440113
ECLASS-13.0	27440113



https://www.phoenixcontact.com/us/products/1415775



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1415775



Accessories

C-SCFFI 2,5/6,3X0,8 - Connector

3240547

https://www.phoenixcontact.com/us/products/3240547



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm², for plug 6.3 x 0.8 mm

C-SCFFI 6/6,3X0,8 - Connector

3240541

https://www.phoenixcontact.com/us/products/3240541



Slip-on sleeve, fully insulated, yellow, 4 ... 6 mm², for 6.3 x 0.8 mm plugs



https://www.phoenixcontact.com/us/products/1415775



C-SCFFI 1,5/6,3X0,8 - Connector

3240538

https://www.phoenixcontact.com/us/products/3240538



Slip-on sleeve, fully isolated, red, 0.5 ... 1.5 mm^2 , for plug 6.3 x 0.8 mm

C-SCFFI 2,5/4,8X0,8 - Connector

3240540

https://www.phoenixcontact.com/us/products/3240540



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm², for plug 4.8 x 0.8 mm



https://www.phoenixcontact.com/us/products/1415775



C-SCFFI 2,5/4,8X0,5 - Connector

3240539

https://www.phoenixcontact.com/us/products/3240539



Slip-on sleeve, fully isolated, blue, 1.5 ... 2.5 mm^2 , for plug 4.8 x 0.5 mm

C-SCFFI 1,5/4,8X0,8 - Connector

3240537

https://www.phoenixcontact.com/us/products/3240537



Slip-on sleeve, fully isolated, red, 0.5 \dots 1.5 mm², for plug 4.8 x 0.8 mm



https://www.phoenixcontact.com/us/products/1415775



C-SCFFI 1,5/4,8X0,5 - Connector

3240536

https://www.phoenixcontact.com/us/products/3240536



Slip-on sleeve, fully isolated, red, 0.5 ... 1.5 mm², for plug 4.8 x 0.5 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com