



Switches > Push Button Switches > Push Button Switch, Socket, 1 Actuator, Flush Profile



Configuration (Pole-Throw): **Single Pole - Double Throw**

Push Button Switch Product Type: **General Purpose Push Button Switch**

Number of Actuators: **Single**

Actuator Profile: **Flush**

Bushing Style: **Plain**

[All Push Button Switch, Socket, 1 Actuator, Flush Profile \(7\)](#)

Features

Product Type Features

Switch Connection Type	DIN Connector
Push Button Switch Product Type	General Purpose Push Button Switch
Illuminated	With
Actuator Style	Round

Configuration Features

Configuration (Pole-Throw)	Single Pole - Double Throw
Number of Actuators	Single
Snap Action	Without
Support Bracket	Without
Switch Feedback Type	Non-Tactile
Operating Function	Momentary

Electrical Characteristics

Contact Current Rating	5 A
Operating Voltage Range	9 – 32 VDC

Body Features

Actuator Force	3060 – 4589 g[108 – 162.8 oz]
----------------	-------------------------------



Actuator Profile	Flush
Bushing Style	Plain
Actuator Color	Green

Contact Features

Switch Contact Plating Material	Silver Alloy
---------------------------------	--------------

Housing Features

Process Sealed	No
----------------	----

Operation/Application

Actuator Total Travel	2.5 mm[.098 in]
-----------------------	-----------------

Packaging Features

Packaging Method	Bulk
------------------	------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (38% in HS10) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # CAT-AL8-STPBSC
Push Button Switch, Center Thread, 1 Actuator, Flush Profile

Also in the Series | KISSLING Series TS

Push Button Switches(73)

Customers Also Bought

TE Part #1718230-1
1,5MM PIN HSG 5-7 POS ASSY

TE Part #3-1393115-2
KUL-11D15D-24=KU

TE Part #1-2364574-9
AVH19 FLT SS MT PWR BLU 24V16A

TE Part #0462-005-20141
SOC, SOLID, SIZE 20, 16-18AWG, NI

TE Part #K1060243
Relay 29-014-12-919

TE Part #K1156175
Batt. Disconnect 35-514-231-R-A5-904

TE Part #K1156657
Emergency Switch ES-2012-A111 900

TE Part #0411-240-2005
EXT TOOL, SIZE 20, 16-22 AWG, N, RED

TS-111-GN32

Single Pole - Double Throw Configuration (Pole-Throw), General Purpose Push Button Switch, Single Actuator, KISSLING Series TS, Push Button Switches



Documents

Product Drawings

Push button switch TS-111-GN32

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_TS-111-GN32_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_TS-111-GN32_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_TS-111-GN32_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

KISSLING PUSH BUTTON SWITCH Series TS

English