



HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY (TE)
TFE-26-X-STK
Raychem | TFE

TFE-26-X-STK
TE Internal Number: 5950032003
Alias ID: 6-1194703-8

EU RoHS Compliant
EU ELV Compliant

Wall Type Single
Resistant To Fluids, Mechanical Damage
Low Outgassing No
Product Source Ireland
Packaging Method Stick

DOCUMENTATION

Catalog Pages/Data Sheets

TFE And TFER Pages From 9-1773447-9
PDF
English

At-Application-Tooling-For-Raychem-Heat-Shrink-Product-2-1773452-8
PDF
English

Product Specifications
Product Specification

TFE Sleeving
PDF
English

Instruction Sheets

Global Dimensional Life For RAYCHEM Heat Shrink Tubing Standard Size Products (Customer Distribution)

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Wall Type Single
Product Family TFE

Electrical Characteristics

Voltage (Max) (kV) .6

Body Features

Shrink Ratio 1.8:1
Color Clear
Flexibility Flexible
Material Polytetrafluoroethylene (PTFE)
Fluid Type Chemicals/Solvents, Water

Dimensions

Expanded Inside Diameter (Min) 1.1 mm [.043 in]
Recovered Inside Diameter (Max) .56 mm [.022 in]
Recovered Wall Thickness (Tolerance) .25 mm [.01 in]
Cut Length 1220 mm [48.031 in]

Usage Conditions

Shrink Temperature (Min) (°C) 340
Resistant To Fluids, Mechanical Damage
Recovery Temperature (°C) 340
Operating Temperature Range (°C) -65 – 250
Flammability Flame-Retardant
Fluid Resistance Splash Protection

Product Availability

Applicable Region Global

Packaging Features

Packaging Method Stick

Other

Low Outgassing No
Product Source Ireland



Statement of Compliance

Statement of Compliance

PDF
