

CII | CII FCB-405 Series

TE Internal #: 1617761-3

General Purpose Power Relay, DC, Polarized, Monostable, 4 Form C 4PDT-CO, 5 A Contact Rating, 28 VDC Coil Voltage, CII FCB-405

Series

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Coil Magnetic System: Polarized, Monostable
Contact Arrangement: 4 Form C 4PDT-CO

Current Type: DC

Contact Current Rating: 5A

Features

Product Type Features	
Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Relay Options	Back EMF Suppression
Coil Special Features	Coil Suppression Diode
Contact Arrangement	4 Form C 4PDT-CO
Electrical Characteristics	
Coil Resistance	400 Ω
Contact Current Rating	5 A
Coil Voltage Rating	28 VDC
Body Features	
Enclosure Type	Hermetically Sealed
Contact Features	
Terminal Plating	Tin-Lead

Silver Cadmium Oxide

Solder Pins

Solder Pins

Contact Material

Termination Features

Main Termination & Connection Type



Mechanical Attachment

Product Mount Type	Printed Circuit Board
Usage Conditions	
Operating Temperature Range	-70 – 125 °C[-94 – 257 °F]
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Vibration Resistance	30G's, 70 – 3000Hz
Shock Resistance	200G's, 6ms
Coil Magnetic System	Polarized, Monostable
Current Type	DC

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | CII FCB-405 Series



Customers Also Bought

















Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1617761-3_B.2d_dxf.zip

English



Customer View Model

ENG_CVM_CVM_1617761-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1617761-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5_sec5_FCB-405

English

RELAY

English