

product type designation
product description

Power M12 Cable Connector PRO
M12 power connector socket, 4-pole, A-coded
IE Power M12 Cable Connector PRO connection socket for connection of SCALANCE W-700/X208PRO for DC 24 V supply voltage 4-pole, A-coded, with installation instructions, 3 units.



suitability for use
For connection to SCALANCE W-700 / X208PRO for 24 V DC voltage supply

interfaces	
number of electrical connections	
• for network components or terminal equipment	1
type of electrical connection	
• for PROFIBUS cables	Integrated screw contacts for 2-core power cables
• for network components or terminal equipment	M12 connector (female insert, A-coded, 4-pin)
type of electrical connection / FastConnect	No

mechanical data	
material / of the enclosure	plastic
locking mechanism design	Screwed joint
tightening torque / for M12 round connector / maximum	0.6 N·m
connector coding / of the M12 circular connector	A

design, dimensions and weights	
type of cable outlet	180° cable outlet
width	19 mm
height	19 mm
depth	73 mm
net weight	40 g
connectable cable cross-section	6 ... 8 mm
connectable conductor cross-section	0.75 mm²
• solid	0.75 mm²
• finely stranded / with core end processing	0.75 mm²
• finely stranded / without core end processing	0.75 mm²

ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
chemical resistance	
• to water	resistant
protection class IP	IP65/67

product features, product functions, product components / general	
product feature	
• silicon-free	Yes
product component	
• strain relief	Yes

standards, specifications, approvals	
--------------------------------------	--

certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• railway application in accordance with EN 50155	No

further information / internet links

internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
----------------------	---

Approvals / Certificates

General Product Approval	Test Certificates	Environment	Industrial Communication
Declaration of Conformity 	 Special Test Certificate	Confirmation	PROFINET

last modified: 7/29/2024 