

MULTI-BEAM

TE Internal #: 6450540-1
Header, Receptacle, Board-to-Board, 26 Position, 2.54 mm [.1 in]
Centerline, Printed Circuit Board, UL 94V-0, Rectangular Power
Connectors

[View on TE.com >](#)



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**
Connector & Housing Type: **Receptacle**
Connector System: **Board-to-Board**
Number of Positions: **26**
Centerline (Pitch): **2.54 mm [.1 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	26
PCB Mount Orientation	Vertical
Number of Power Positions	2
Number of Signal Positions	24
Number of Rows	4

Electrical Characteristics

Operating Voltage	60 VDC
-------------------	--------

Contact Features

Power Contact Base Material	Tin
Contact Underplating Material Thickness	3.43 μm
Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
Contact Underplating Material	Nickel



Contact Current Rating (Max)	42 A
Contact Retention Within Housing	Without
Contact Type	Receptacle
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.076 μm[3 μin]

Termination Features

Termination Post & Tail Length	3.43 mm[.135 in]
Termination Method to PCB	Through Hole - Press-Fit

Mechanical Attachment

PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail, Boardlock
Mating Retention Type	Action/Compliant Tail, Boardlock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Black
Housing Material	High Temperature Thermoplastic

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
--------------------	----------------

Usage Conditions

Operating Temperature Range	-20 – 105 °C[-4 – 221 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	High Temperature Part - Not Glow Wire

Packaging Features

Packaging Method	Tray
------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 6450330-1
MBXL R/A HDR 1P+24S+1P

TE Part # 6600330-4
MBXL VERT HDR 1P+24S+1P

TE Part # 1600236-4
PAN MT PLUG, MBXL, 1P+24S+1P

TE Part # 1600820-1
STL W/GUIDES, MBXL, 1P+24S+1P


TE Part # 6450500-5
MBXL VERT HDR 1P+24S+1P

Customers Also Bought





TE Part #1-350777-2
02P UMNL V0 PLUG HSG RED



TE Part #6450160-3
MBXL R/A RCPT 1P+24S+1P



TE Part #6600330-4
MBXL VERT HDR 1P+24S+1P



TE Part #350923-6
UMNL SOK 12-10 AUNI/PHBZ



TE Part #1-350777-3
02P UMNL V0 PLUG HSG ORANGE



TE Part #1-350777-9
02P UMNL V0 PLUG HSG BLACK



TE Part #1-534998-8
36 MODIV VRT DR CE 100/125



TE Part #2-31890-1
PIDG R 22-16 COMM 22-18 MIL 8



TE Part #1-338088-6
8/8 INV.MOD.JACK



TE Part #1-350777-8
02P UMNL V0 PLUG HSG GRAY

Documents

Product Drawings

MBXL VERT RCPT 1P+24S+1P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6450540-1_F_c-6450540-1-f.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6450540-1_F_c-6450540-1-f.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6450540-1_F_c-6450540-1-f.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



POWER_CONNECTORS_CATALOG_SEC01_BOARD_TO_BOARD

English

MULTI-BEAM XL Cable Plug Assemblies Datasheet 6-1773442-7

English

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English