

Part Number : 29110042

**Product Description :** 2.50mm Pitch Mini-Latch Wire-to-Wire Plug Housing, Friction Lock, with Mounting Ears, 4 Circuits, Natural

Series Number: 5240

**Status:** New Business Not Supported

**Product Category:** Connector Housings

**Engineering Number: 5240-04** 

### **Documents & Resources**

## **Product Environment Compliance**

## Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

### **Part Details**

#### General

Status	New Business Not Supported
Category	Connector Housings

Series	5240
Description	2.50mm Pitch Mini-Latch Wire-to- Wire Plug Housing, Friction Lock, with Mounting Ears, 4 Circuits, Natural
Application	Signal, Wire-to-Wire
Product Family	Mini-Latch Wire-to-Board / Wire-to- Wire Connector System
Product Name	Mini-Latch
UPC	800753585119

# Agency

CSA	LR19980
UL	E29179

# Physical

Circuits (maximum)	4
Color - Resin	Natural (White)
Flammability	94V-0
Gender	Plug
Glow-Wire Capable	No
Lock to Mating Part	Yes
Net Weight	997.200/mg
Number of Rows	1
Packaging Type	Bag
Panel Mount	Yes
Pitch - Mating Interface	2.50mm
Stackable	No
Temperature Range - Operating	-40° to +105°C