

12, 16 and 19-Pin multifast® Field Wireable In-line Connectors

- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP65 Protection



Housing Style	Female Part Number	Features	Pinout
	CK 12-0	Nickel plated brass, PG 11 cable gland, accepts 4-10 mm cable diameter, accepts up to 12x18 AWG conductors, 125°C, 300 V, 8.0 A, field wireable 12-pin in-line connector, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	Female
	CK 16-0	Nickel plated brass, PG 13.5 cable gland, accepts 5-12 mm cable diameter, accepts up to 16x18 AWG conductors, 125°C, 150 V, 8.0 A, field wireable 16-pin in-line connector, for use with <i>eurofast</i> ® (isolated power supply) junctions boxes	Female
	CK 19-0	Nickel plated brass, PG 13.5 cable gland, accepts 5-12 mm cable diameter, accepts up to 19x18 AWG conductors, 125°C, 150 V, 8.0 A, field wireable 19-pin in-line connector, for use with <i>eurofast</i> ® (two Signals per port) junctions boxes	Female
	CK 125-0	Nickel plated brass, IAC, accepts 3-10 mm cable diameter accepts up to 12x18 AWG conductors, 125°C, 150 V, 8.0 A, field wireable 12-pin in-line connector	Female