


**SERIES****0925R**  
**0925****Molded Shielded RF Coils**

Actual Size

**Military Specifications**

MS21426 (LT10K); MS21427 (LT10K)

**Physical Parameters**

|             | Inches         | Millimeters   |
|-------------|----------------|---------------|
| Length      | 0.250 ± 0.010  | 6.35 ± 0.25   |
| Diameter    | 0.095 ± 0.010  | 2.41 ± 0.25   |
| Lead Size   |                |               |
| AWG #24 TCW | 0.020 ± 0.0015 | 0.508 ± 0.038 |
| Lead Length | 1.5 ± 0.12     | 38.10 ± 3.05  |

**Current Rating at 90°C Ambient** 15°C Rise**Operating Temperature Range** -55°C to +105°C**Maximum Power Dissipation at 90°C** 0.0585 W**Weight Max.** (Grams) 0.25**Incremental Current** Current level which causes a Max. of 5% change in inductance.**Coupling** 3% Max.

† Self Resonant Frequency (SRF) values are calculated and to be used for reference only.

**Marking** DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 0925R-472K

|               |                 |
|---------------|-----------------|
| <i>Front:</i> | <i>Reverse:</i> |
| DELEVAN       | 4.7uH±10%       |
| 4.7uH±10%     | R 0902A         |

**Packaging** Tape & reel: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.**Made in the U.S.A.**

| DASH NUMBER*                                       | MIL DASH # | INDUCTANCE (μH) ±10% | TEST FREQUENCY (MHz) | Q MINIMUM | SRF MINIMUM (MHz) | DC RESISTANCE MAXIMUM (OHMS) | CURRENT RATING MAXIMUM (mA) | INCREMENTAL CURRENT (mA) |
|----------------------------------------------------|------------|----------------------|----------------------|-----------|-------------------|------------------------------|-----------------------------|--------------------------|
| MS21426- SERIES 0925 IRON CORE & SLEEVE (LT10K)    |            |                      |                      |           |                   |                              |                             |                          |
| -101K                                              | 1          | 0.10                 | 54                   | 25.0      | 490.0†            | 0.10                         | 670                         | 670                      |
| -121K                                              | 2          | 0.12                 | 52                   | 25.0      | 430.0†            | 0.11                         | 635                         | 635                      |
| -151K                                              | 3          | 0.15                 | 50                   | 25.0      | 415.0†            | 0.12                         | 610                         | 610                      |
| -181K                                              | 4          | 0.18                 | 49                   | 25.0      | 375.0†            | 0.13                         | 585                         | 585                      |
| -221K                                              | 5          | 0.22                 | 47                   | 25.0      | 330.0†            | 0.15                         | 545                         | 545                      |
| -271K                                              | 6          | 0.27                 | 46                   | 25.0      | 300.0†            | 0.16                         | 530                         | 530                      |
| -331K                                              | 7          | 0.33                 | 44                   | 25.0      | 260.0†            | 0.18                         | 495                         | 495                      |
| -391K                                              | 8          | 0.39                 | 42                   | 25.0      | 230.0             | 0.19                         | 485                         | 485                      |
| -471K                                              | 9          | 0.47                 | 41                   | 25.0      | 220.0             | 0.21                         | 460                         | 460                      |
| -561K                                              | 10         | 0.56                 | 41                   | 25.0      | 210.0             | 0.23                         | 440                         | 440                      |
| -681K                                              | 11         | 0.68                 | 39                   | 25.0      | 180.0             | 0.24                         | 430                         | 430                      |
| -821K                                              | 12         | 0.82                 | 38                   | 25.0      | 165.0             | 0.27                         | 405                         | 405                      |
| -102K                                              | 13         | 1.00                 | 37                   | 25.0      | 150.0             | 0.30                         | 385                         | 385                      |
| -122K                                              | 14         | 1.20                 | 40                   | 7.9       | 130.0             | 0.73                         | 247                         | 247                      |
| -152K                                              | 15         | 1.50                 | 41                   | 7.9       | 115.0             | 0.86                         | 228                         | 228                      |
| -182K                                              | 16         | 1.80                 | 43                   | 7.9       | 105.0             | 0.95                         | 217                         | 217                      |
| -222K                                              | 17         | 2.20                 | 45                   | 7.9       | 95.0              | 1.10                         | 202                         | 202                      |
| -272K                                              | 18         | 2.70                 | 48                   | 7.9       | 90.0              | 1.20                         | 193                         | 193                      |
| -332K                                              | 19         | 3.30                 | 49                   | 7.9       | 80.0              | 1.30                         | 185                         | 185                      |
| -392K                                              | 20         | 3.90                 | 50                   | 7.9       | 75.0              | 1.50                         | 173                         | 173                      |
| -472K                                              | 21         | 4.70                 | 53                   | 7.9       | 70.0              | 2.40                         | 136                         | 136                      |
| -562K                                              | 22         | 5.60                 | 54                   | 7.9       | 60.0              | 2.90                         | 124                         | 124                      |
| -682K                                              | 23         | 6.80                 | 55                   | 7.9       | 55.0              | 3.20                         | 118                         | 118                      |
| -822K                                              | 24         | 8.20                 | 55                   | 7.9       | 53.0              | 3.60                         | 111                         | 111                      |
| -103K                                              | 25         | 10.0                 | 57                   | 7.9       | 50.0              | 4.00                         | 106                         | 106                      |
| -123K                                              | 26         | 12.0                 | 36                   | 2.5       | 35.0              | 3.00                         | 122                         | 122                      |
| -153K                                              | 27         | 15.0                 | 38                   | 2.5       | 30.0              | 3.40                         | 115                         | 115                      |
| -183K                                              | 28         | 18.0                 | 40                   | 2.5       | 26.0              | 3.80                         | 108                         | 108                      |
| -223K                                              | 29         | 22.0                 | 40                   | 2.5       | 24.0              | 4.90                         | 96                          | 96                       |
| -273K                                              | 30         | 27.0                 | 40                   | 2.5       | 21.0              | 5.80                         | 88                          | 88                       |
| -333K                                              | 31         | 33.0                 | 41                   | 2.5       | 20.0              | 6.50                         | 83                          | 83                       |
| -393K                                              | 32         | 39.0                 | 42                   | 2.5       | 19.0              | 7.90                         | 75                          | 75                       |
| -473K                                              | 33         | 47.0                 | 44                   | 2.5       | 16.0              | 9.30                         | 69                          | 69                       |
| -563K                                              | 34         | 56.0                 | 44                   | 2.5       | 15.0              | 11.0                         | 64                          | 64                       |
| -683K                                              | 35         | 68.0                 | 45                   | 2.5       | 13.0              | 12.0                         | 61                          | 61                       |
| -823K                                              | 36         | 82.0                 | 45                   | 2.5       | 11.0              | 13.0                         | 59                          | 59                       |
| -104K                                              | 37         | 100.0                | 40                   | 2.5       | 10.5              | 16.8                         | 51                          | 51                       |
| MS21427- SERIES 0925 FERRITE CORE & SLEEVE (LT10K) |            |                      |                      |           |                   |                              |                             |                          |
| -124K                                              | 1          | 120.0                | 31                   | 0.79      | 13.0              | 5.80                         | 88                          | 27                       |
| -154K                                              | 2          | 150.0                | 33                   | 0.79      | 12.0              | 7.90                         | 75                          | 24                       |
| -184K                                              | 3          | 180.0                | 33                   | 0.79      | 11.0              | 9.40                         | 69                          | 22                       |
| -224K                                              | 4          | 220.0                | 35                   | 0.79      | 10.0              | 11.0                         | 64                          | 20                       |
| -274K                                              | 5          | 270.0                | 37                   | 0.79      | 9.0               | 12.0                         | 61                          | 18                       |
| -334K                                              | 6          | 330.0                | 40                   | 0.79      | 8.0               | 16.0                         | 53                          | 16                       |
| -394K                                              | 7          | 390.0                | 38                   | 0.79      | 7.8               | 21.0                         | 46                          | 14                       |
| -474K                                              | 8          | 470.0                | 36                   | 0.79      | 7.5               | 24.0                         | 43                          | 13                       |
| -564K                                              | 9          | 560.0                | 36                   | 0.79      | 7.0               | 28.0                         | 40                          | 12                       |

**Parts listed above are QPL/MIL qualified**

Optional Tolerances: J = 5% H = 3%

\*Complete part # must include series # PLUS the dash #

For surface finish information, refer to [www.delevanfinishes.com](http://www.delevanfinishes.com)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## API Delevan:

[MS21426-13](#) [MS21426-19](#) [MS21426-35](#) [0925-222K](#) [0925-183K](#) [0925-101K](#) [0925-101J](#) [0925-101H](#) [0925-101G](#)  
[0925-101F](#) [0925-121K](#) [0925-121J](#) [0925-121H](#) [0925-121G](#) [0925-121F](#) [0925-151K](#) [0925-151J](#) [0925-151H](#) [0925-](#)  
[151G](#) [0925-151F](#) [0925-181K](#) [0925-181J](#) [0925-181H](#) [0925-181G](#) [0925-181F](#) [0925-221K](#) [0925-221J](#) [0925-221H](#)  
[0925-221G](#) [0925-221F](#) [0925-271K](#) [0925-271J](#) [0925-271H](#) [0925-271G](#) [0925-271F](#) [0925-331K](#) [0925-331J](#) [0925-](#)  
[331H](#) [0925-331G](#) [0925-331F](#) [0925-391K](#) [0925-391J](#) [0925-391H](#) [0925-391G](#) [0925-391F](#) [0925-471J](#) [0925-471H](#)  
[0925-471G](#) [0925-471F](#) [0925-561K](#) [0925-561J](#) [0925-561H](#) [0925-561G](#) [0925-561F](#) [0925-681K](#) [0925-681J](#) [0925-](#)  
[681H](#) [0925-681G](#) [0925-681F](#) [0925-821K](#) [0925-821J](#) [0925-821H](#) [0925-821G](#) [0925-821F](#) [0925-102J](#) [0925-102H](#)  
[0925-102G](#) [0925-102F](#) [0925-122K](#) [0925-122J](#) [0925-122H](#) [0925-122G](#) [0925-122F](#) [0925-152K](#) [0925-152J](#) [0925-](#)  
[152H](#) [0925-152G](#) [0925-152F](#) [0925-182J](#) [0925-182H](#) [0925-182G](#) [0925-182F](#) [0925-222J](#) [0925-222H](#) [0925-222G](#)  
[0925-222F](#) [0925-272J](#) [0925-272H](#) [0925-272G](#) [0925-272F](#) [0925-332J](#) [0925-332H](#) [0925-332G](#) [0925-332F](#) [0925-](#)  
[392K](#) [0925-392J](#) [0925-392H](#) [0925-392G](#) [0925-392F](#) [0925-472K](#)