

1202888

https://www.phoenixcontact.com/us/products/1202888

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimping tool, for turned contacts, universal cross-section setting, up to a maximum of 6.0 mm<sup>2</sup>, digital display with 0.01 mm increments, pressure lock can be unlocked, positioning tool necessary as an accessory for contact positioning

# Your advantages

- · Electronic wear monitoring with recalibration function
- · Process reliability with pressure lock and setting lock
- · Basic setting testing with accompanying test pin
- · Safe and simple handling with digital display and optional positioning aid
- · Rotating positioning aid ensures precise contact positioning in the crimping area

### Commercial data

Item number	1202888
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH3135
GTIN	4063151267711
Weight per piece (including packing)	1,140.7 g
Weight per piece (excluding packing)	1,140.7 g
Customs tariff number	82032000
Country of origin	DE



1202888

https://www.phoenixcontact.com/us/products/1202888

# Technical data

#### Notes

Note on application	The packing slip includes a detailed list of crimp contacts for turned crimp contacts from 0.14 mm <sup>2</sup> 4.0 mm <sup>2</sup> of the series CK1.6 ED, CK2.5 ED, CK4.0 ED, CC1.5-TS-2,10, CC1.5-TS-2,50,
Note on application	Use with locator only; see accessories for selection
Utilization restriction	
EMC note	EMC: class A product, see manufacturer's declaration in the download area

### Product properties

Product type	Crimping tool
Compression	Four-mandrel crimping
Crimping position 1	
Chimping position 1	
Min. cross section	0.14 mm <sup>2</sup>
Max. cross section	6 mm <sup>2</sup>
AWG min	26
AWG max	10

### Connection data

#### Conductor connection

Cross section range, metric	0.14 mm² 6 mm²
Cross section range AWG	26 10

### **Dimensions**

Width	94 mm
Height	28 mm
Length	236 mm

### Material specifications

Color	black (RAL 9005)
Material	Steel



1202888

https://www.phoenixcontact.com/us/products/1202888

# **Approvals**

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1202888



EAC

Approval ID: RU x-DE.xx08.B.02974



1202888

https://www.phoenixcontact.com/us/products/1202888

# Classifications

### **ECLASS**

UNSPSC 21.0

	ECLASS-11.0	21043811
	ECLASS-12.0	21043811
	ECLASS-13.0	21043811
ETIM		
	ETIM 9.0	EC000168
UN	ISPSC	

27111500



1202888

https://www.phoenixcontact.com/us/products/1202888

# Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	894d1c6f-7088-4bbd-a917-a42c74c7be7c

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com