### Buchanan

TE Internal #: 796689-5

Header, Wire-to-Board, 5 Position, 5 mm [.197 in] Centerline, 1 Row, 35° Wire Entry Angle, 30 – 12 AWG Wire Size, PCB Terminal

Blocks

View on TE.com >




Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 5

Centerline (Pitch): 5 mm [ .197 in ]

Number of Rows: 1

### **Features**

## **Product Type Features**

Wire Protection	With
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacked Levels	Without
Wire Entry Location	Side
Stacking Configuration	Side Stackable
Number of Positions	5
Number of Rows	1
Wire Entry Angle	35°
Electrical Characteristics	
Operating Voltage	300 VAC



Primary Product Color	Black
Product Orientation	Vertical
Contact Features	
Contact Mating Area Plating Material	Tin
Contact Base Material	Brass
Contact Current Rating (Max)	17.5 A
Termination Features	
Termination Post & Tail Length	3.8 mm[.15 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Screw Plating Material	Nickel
Screw Material	Brass
Thread Size	M3
Thread Size  Connector Mounting Type	M3 Board Mount
Connector Mounting Type	
Connector Mounting Type  Housing Features	Board Mount
Connector Mounting Type  Housing Features  Housing Material	Board Mount  PA 66
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)	Board Mount  PA 66
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions	PA 66 5 mm[.197 in]
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions  Wire Size	PA 66 5 mm[.197 in]
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions  Wire Size  Usage Conditions	Board Mount  PA 66 5 mm[.197 in]  .05 – 3 mm <sup>2</sup>
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions  Wire Size  Usage Conditions  Operating Temperature Range	Board Mount  PA 66 5 mm[.197 in]  .05 – 3 mm <sup>2</sup>
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions  Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application	Board Mount  PA 66  5 mm[.197 in]  .05 – 3 mm <sup>2</sup> -40 – 110 °C[-40 – 230 °F]
Connector Mounting Type  Housing Features  Housing Material  Centerline (Pitch)  Dimensions  Wire Size  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application	Board Mount  PA 66  5 mm[.197 in]  .05 – 3 mm <sup>2</sup> -40 – 110 °C[-40 – 230 °F]

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions



China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (.8% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Customers Also Bought
























### **Documents**

### **Product Drawings**

TERMI-BLOK PCB MOUNT 5P.

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_796689-5\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_796689-5\_A.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_796689-5\_A.2d\_dxf.zip

English

3D PDF

English

**Customer View Model** 

ENG\_CVM\_CVM\_796689-5\_A1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_796689-5\_A1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_796689-5\_A1.3d\_igs.zip

English

3D PDF

3D



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

**BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS** 

English

1-1773458-1\_EURO\_STYLE\_TERMINAL\_BLOCKS\_QRG

English

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

UL

English