What can we help you find?

🗓 Share

Quick Links

Pricing & Availability

Product Feature Selector

Contact Us About This Product

Search for Tooling

Email

Feedback

Print

Products Innovation Industries Resources About TE My Account Support Center

Home > Products > Tubing & Harnessing Products > Product Feature Selector > Product Details

RW-200-3/8-0-SP Product Details



TE Internal Number: CB7765-000

Active

Heat Shrink Tubing

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = RW-200
- Product Source = U.K., U.S.
- Flexible
- Medium Wall Style

View all Features

Add to My Part List Request Sample Find Similar Products

Documentation & Additional Information

Product Drawings:

RW-200 Tubing-Heat-Shrinkable Chemical-Resistant, Hi... (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Tooling

Related Products:

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Heat Shrinkable Tubing
- Color = Black

Dimensions:

- Inside Diameter (Min-Max) (mm [in]) = 4.75 9.53 [0.187 0.375]
- Expanded ID, Min. (mm [in]) = 9.53 [0.375]
- Recovered ID, Max. (mm [in]) = 4.80 [0.189]
- Length (M [ft]) = 30.48 [100.00]

Body Features:

- Product Name = RW-200 Pliancy = Flexible
- Wall Style = Medium
- Wall Type = Single
- Material = Crosslinked Fluoroelastomer
- Shrink Ratio = 2:1
- Fluid Type = Aviation Fuel, Brake Fluid, Chemicals/Solvents, Hydraulic Fluid, Lubricating Oil, Water
- Resistant To = Abrasion, Fluids, Wrinkling

Housing Features:

- Material Systems = Yes
- Material Systems Code = 200

Industry Standards:

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M23053/13-003-0 Flammability Rating Type = Highly Flame-Resistant
- UL Rating = None
- CSA Certified = No
- Approved Standards = AMS-DTL 23053/13, NASA SP-R-0022A
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- · Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Fluid Resistance = Splash Protection
- Operating Temperature (°C) = -40 +200

Conditions for Usage:

List all Documents

- Full Recovery Temperature (°C) = 175
- Shrink Temperature, Min. (°C) = 100
- High Temperature Compatible = Yes

Operation/Application:

- Application = Cable Jacketing, Wire Bundling
- Emission Free = No
- Product Use = Cables, Harnesses

Packaging Features:

Packaging Method = Spool

Product Availability:

Product Source = U.K., U.S.

Other:

Brand = Raychem

Corporate Information

About TE

Investors

News Room

Supplier Portal

Careers

Terms & Conditions

Privacy Policy

AODA Accessibility Policy

AODA Multi-Year Accessibility

Quick Links

Distributor Inventory

Product Cross Reference

Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base

Manage Your Account

Keep Me Informed

