

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 48 ...](#) » [SK 48](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - [Standard extruded heatsinks](#)
 - Extruded heatsinks for lock-in retaining spring
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components

▶ Cases f.case

▶ Connectors f.con

Standard extruded heatsinks

SK 48 ...

SK 48 50 SA

65 x 20 mm

Data sheet

add to request



Features

Technical Drawing

Service

thermal resistance R_{th}	3.5 - 2 K/W
drilling pattern	SSR 3 TO 3 CB
surface	black anodised
height	20 mm
width B	65 mm
length	50 mm
plate thickness	4 mm