

PDX316IEC-960

APC Modular IT Power Distribution Cable Extender 3 Wire 16A IEC309 960cm



Overview

Model Name	APC Modular IT Power Distribution Cable Extender 3 Wire 16A IEC309 960cm
Standard Lead Time	Usually Ships within 3 Weeks
Product Distribution	Afghanistan , Albania , Algeria , Andorra , Angola , Armenia , Australia , Austria , Azerbaijan , Bahrain , Bangladesh , Belarus , Belgium , Benin , Bhutan , Bosnia And Herzegovina , Botswana , Brunei Darussalam , Bulgaria , Burkina Faso , Burundi , Cameroon , Central African Republic , Chad , China , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , East Timor , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Fiji , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hong Kong , Hungary , Iceland , India , Indonesia , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Malaysia , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova , Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Papua New Guinea , Philippines , Poland , Portugal , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sri Lanka , Sudan , Suriname , Sweden , Switzerland , Taiwan , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Nominal Output Voltage	230V
Maximum Total Current Draw per Phase	16 A
Output Connections	(1) IEC 309 16A (2P+E) (Battery Backup)
Always on Outlets	0

Input

Nominal Input Voltage	230V
Input Connections	IEC 309 16A 2P+E
Number of Power Cords	0
Maximum Line Current per phase	16 A
Maximum Input Current per phase	0 A
Load Capacity	0 VA

Physical

Net Weight	2.19 kg
Maximum Height	152.0 mm
Maximum Width	432.0 mm
Maximum Depth	406.0 mm
Shipping Weight	3.1 kg
Shipping Height	152.0 mm
Shipping Width	432.0 mm
Shipping Depth	406.0 mm

Conformance

Approvals	CE
Standard warranty	1 year repair or replace