




N-Channel 100-V (D-S) 175°C MOSFET


PRODUCT SUMMARY

V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
100	0.200 @ $V_{GS} = 10$ V	6.5
	0.225 @ $V_{GS} = 4.5$ V	6.0

175°C Rated
Maximum Junction Temperature
TrenchFET®
Power MOSFETs



Order Number:
SUU06N10-225L



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	100	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$) ^b	$T_C = 25^\circ\text{C}$	I_D	6.5	A
	$T_C = 125^\circ\text{C}$		3.75	
Pulsed Drain Current		I_{DM}	8.0	
Continuous Source Current (Diode Conduction)		I_S	6.5	
Avalanche Current		I_{AR}	5.0	mJ
Repetitive Avalanche Energy (Duty Cycle $\leq 1\%$)		E_{AR}	1.25	
Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	20 ^b	W
	$T_A = 25^\circ\text{C}$		1.5 ^a	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter		Symbol	Typical	Maximum	Unit
Junction-to-Ambient ^a	$t \leq 10$ sec	R_{thJA}	40	50	$^\circ\text{C/W}$
	Steady State		80	100	
Junction-to-Case		R_{thJC}	6.0	7.5	

Notes







- a. Surface Mounted on 1" x1" FR4 Board.
b. See SOA curve for voltage derating.






**SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)**

Parameter	Symbol	Test Condition	Min	Typ ^a	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 μA	100			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	1.0		3.0	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 80 V, V _{GS} = 0 V			1	μA
		V _{DS} = 80 V, V _{GS} = 0 V, T _J = 125°C			50	
		V _{DS} = 80 V, V _{GS} = 0 V, T _J = 175°C			250	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	8.0			A
Drain-Source On-State Resistance ^b	r _{DS(on)}	V _{GS} = 10 V, I _D = 3 A		0.160	0.200	Ω
		V _{GS} = 10 V, I _D = 3 A, T _J = 125°C			0.350	
		V _{GS} = 10 V, I _D = 3 A, T _J = 175°C			0.450	
		V _{GS} = 4.5 V, I _D = 1.0 A		0.180	0.225	
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 3 A		8.5		S
Dynamic ^a						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, F = 1 MHz		240		pF
Output Capacitance	C _{oss}			42		
Reverse Transfer Capacitance	C _{rss}			17		
Total Gate Charge ^c	Q _g	V _{DS} = 50 V, V _{GS} = 5 V, I _D = 6.5 A		2.7	4.0	nC
Gate-Source Charge ^c	Q _{gs}			0.6		
Gate-Drain Charge ^c	Q _{gd}			0.7		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 50 V, R _L = 7.5 Ω I _D ≅ 6.5 A, V _{GEN} = 10 V, R _g = 2.5 Ω		7	11	ns
Rise Time ^c	t _r			8	12	
Turn-Off Delay Time ^c	t _{d(off)}			8	12	
Fall Time ^c	t _f			9	14	
Source-Drain Diode Ratings and Characteristic (T _C = 25°C)						
Pulsed Current	I _{SM}				8.0	A
Diode Forward Voltage ^b	V _{SD}	I _F = 6.5 A, V _{GS} = 0 V		0.9	1.3	V
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 6.5 A, di/dt = 100 A/μs		35	60	ns

Notes

- a. Guaranteed by design, not subject to production testing.
b. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
c. Independent of operating temperature.

**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)**

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

THERMAL RATINGS




Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.