

1		2		3		4		5		6		7		8					
SAMZO		REAC/ROHS												REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE
														A1	NEW	Replace frame			2018.06.12

E

D

C

B

A

技术要求:

Technical requirements:

1. 打铜底0.5-1UM, 镍底2-2.5UM, 哑锡3-5UM。

Copper base 0.5 - 1 UM, nickel base 2 - 2.5 UM, matte tin 3 - 5 UM.

2. 不得有脚变形, 毛刺等缺陷。

There shall be no defects such as pin deformation and burrs.

3. 插脚尖部符合可焊性要求。

The tip of the insertion pin shall meet the solderability requirements.

4. 螺纹需符合通止规要求。

The thread shall meet the requirements of the go and no-go gauge.

5. 材质: 黄铜H65。

Material: Brass H65.

6. 过载电流: 75A

Overload current:75A

7. 螺孔为拉伸M4/M5

The screw holes are extruded M4/M5

8. 未标注尺寸公差值按 GB/T1184-1996H级

Unmarked dimensional tolerance values are in accordance with Grade H of GB/T1184-1996

911

SERISE:
9.2*11.1mm

65

FOOT HIGH:
4.0mm

40

HIGH:
6.5mm

1

CUSTOM CODE:
ROUTINE

M*

SCREW HOLE:
M4/M5

9,2

6,5

4,0

5,0

1,6

11,1

10,5

10,1

3,1

1,2

1,0

11,1

9,2

拉伸M4/M5

10,1

5,0

Ø1,8

PCB LAYOUT

ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR							FIRST VIEW				The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM		TITLE:: 9.2*11.1-H6.5+4mm (M4/M5)	
A	Subject	H62(Y2)	1	tin plating													DWG NO: 911-P011	
								GENERAL TOLERANCE				SCALE	1:1	UNIT	mm	PART NO: 911-23052105		
								≥0~2<	±0.15			SAMZO COMPONENTS Electronic switch and connector manufacturer				MODEL NO: 91165401-M*		
					DESIGN	WANGGUIFA	2018.06.12	≥2~5<	±0.25							NAME:		
					CHECKED	ZHENGUILAN	2018.06.12	≥0~2<	±0.15							PCB soldering terminal		
F					APPROVED	LILIANJIANG	2018.06.14	≥5	±0.35									
1		2		3		4		5		6		7		8				