



SECTION A-A

N = Number of poles

Dim A = $N \times 5.0 + 1.5$

Dim B = $N \times 5.0 + 3.2$

Dim C = $(N - 1) \times 5.0$

	Dim A	Dim B	Dim C
2-6p	±0.20	±0.20	±0.20
7-12p	±0.25	±0.25	±0.25
13-18p	±0.30	±0.30	±0.30
19-24p	±0.40	±0.40	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

Material:

- Item a :Terminal body Thermoplastic (UL94 V-0)
- Item b :Terminal body Thermoplastic (UL94 V-0)
- Item c :Male contact pin: Brass Tin plated
- Item d :Spring clamp: Stainless steel

Electrical cULus

- Voltage rating: 300V
- Current rating: 8A
- Wire range:
- Solid wire(AWG): 12-28
- Stranded wire(AWG): 12-28
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +105°C
- Safety Approval:

NB xx 7 0 x 0 xxxx G

02 2 poles
03 3 poles
...
24 24 poles

0 Black
5 Green (RAL6018/T)
6 Blue
8 Grey (RAL7035/D)

RoHS
Pb<40,000ppm

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by customer request, please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		NB 5.0mm series W/O			
PART NO.	NBxx70x0xxxxG			DWG NO.	8NB0001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Runner 2010.04.22	Runner 2010.04.22		Tolerance
					X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X° ±1°

UNIT: mm

SCALE: 2/1

SHEET: 01/01

REV.: B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>NB0270800000G</u>	<u>NB0370800000G</u>	<u>NB0470800000G</u>	<u>NB0570800000G</u>	<u>NB0670800000G</u>	<u>NB0770800000G</u>
<u>NB0870800000G</u>	<u>NB0970800000G</u>	<u>NB1070800000G</u>	<u>NB1170800000G</u>	<u>NB1270800000G</u>	<u>NB1370800000G</u>
<u>NB1470800000G</u>	<u>NB1570800000G</u>	<u>NB1670800000G</u>	<u>NB1770800000G</u>	<u>NB1870800000G</u>	<u>NB1970800000G</u>
<u>NB2070800000G</u>	<u>NB2170800000G</u>	<u>NB2270800000G</u>	<u>NB2370800000G</u>	<u>NB2470800000G</u>	