



Ceramic Stand-Off Insulators for RF-Equipment



FEATURES

- Application in HF equipment
- High flashover voltage
- High compressive and tensile load
- Different thread sizes available

MATERIAL

Stand-off insulator elements made from Class 1 ceramic material (C 221-IEC 60672-3), body completely glazed.

Connection Terminals: Brass

MARKING

None

OPERATING CONDITIONS

Maximum Operating Temperature: + 100 °C

Maximum Compressive Load: 3.0 kN

Maximum Tensile Load: 7.5 kN

Maximum Reactive Current: 3 A_{RMS}

QUICK REFERENCE DATA

DESCRIPTION	VALUE						
Ceramic Class	1						
Ceramic Dielectric	R7						
Type	Stand-off Insulator 3540/6, 3550/6, 3558/6, 3560/6, 3570/6, 3580/6, 35100/6, 35125/6						
Voltage (V _{RMS})	10 000	12 000	13 000	15 000	16 000	19 000	22 000
Min. Capacitance (pF)	2.5	1.9	1.2	0.9	0.7	0.5	0.3
Max. Capacitance (pF)	2.5	1.9	1.2	0.9	0.7	0.5	0.3
Mounting	Screw terminal						

SAP PART NUMBER, ELECTRICAL, AND DIMENSIONAL DATA


PART NUMBER	CERAMIC	CAPACITANCE VALUES (pF)	FLASHOVER VOLTAGE AT 50 Hz, 60 % REL. AIR HUMIDITY (kV _{RMS})	OPERATING VOLTAGE (kV _{RMS})	DIMENSIONS H mm (INCHES)	DISSIPATION FACTOR
ISOLATOR3540M#1	R7	2.5	25	10	40 (1.575)	Max. 0.05 % (1 MHz)
ISOLATOR3550M#1		1.9	29	12	50 (1.969)	
ISOLATOR3558M#1		1.2	33	13	58 (2.283)	
ISOLATOR3560M#1		1.2	33	13	60 (2.362)	
ISOLATOR3570M#1		0.9	37	15	70 (2.756)	
ISOLATOR3580M#1		0.7	41	16	80 (3.150)	
ISOLATOR35100M#1		0.5	48	19	100 (3.937)	
ISOLATOR35125M#1		0.3	56	22	125 (4.921)	

Note

- # indicator of thread size, "6" = M6 (standard), other metric sizes as well as US standard threads are available on request



DIMENSIONS in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.