



Technical requirements
Rated load:DC 16V 0.5A
Switching withstand voltage:AC 500V
Contact resistance:≤300 mΩ
Insulation resistance:≥50 MΩ
Actuating force:30±10gf
Electrical life:50,000 Cycles

$$\frac{7}{\textcircled{1}} \quad \frac{9330}{\textcircled{2}} \quad \frac{1}{\textcircled{3}} \quad \frac{1}{\textcircled{4}} \quad \frac{14}{\textcircled{5}} \quad \frac{1}{\textcircled{6}}$$

- 1.Series: Micro Switch
- 2.Format: Size(mm)
- 3.Welding method: 4P-DIP
- 4.Function: Normally Open (NO)
- 5.Handle length: 14.2mm
- 6.Mould Number: L1

FIRST VIEW

The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts.
WWW.KKK-JP.COM

TITLE::	9.3*3.0*14.3 四脚插件单定位弧形柄
---------	----------------------------

of DWG NO: 79330-PL2010

PART NO: 79330-20120310

MODEL NO:	7933011141
-----------	------------

NAME:	MICRO SWITCH
-------	--------------

SAMZO COMPONENTS
Electronic switch and connector manufacturer