

<p>? None Available</p> <p>Product Specifications:</p> <p>? None Available</p> <p>Application Specifications:</p> <p>? None Available</p> <p>Instruction Sheets:</p> <p>? None Available</p> <p>CAD Files:</p> <p>? None Available</p>	<p>List all Documents</p>
--	---

<div>Product Features</div> <div>(Please use the Product Drawing for all design activity)</div>	
<div>Product Type Features:</div> <div> <div>? Cable Style = Primary</div> <div>? Number of Conductors = Twisted Pair</div> </div> <div>Electrical Characteristics:</div> <div> <div>? Voltage Rating (VAC) = 600</div> </div> <div>Body Related Features:</div> <div> <div>? Wire Size (AWG/CM) = 24 AWG</div> <div>? Conductor Type = Tin -Coated Copper</div> <div>? Wire Color = Red, White</div> <div>? Outside Diameter (mm [in]) = 2.03 [0.080]</div> <div>? Wire Diameter (mm [in]) = 1.02 [0.040]</div> <div>? Conductor O.D. (mm [in]) = 0.64 [0.025]</div> </div> <div>Configuration Related Features:</div> <div> <div>? Cable Type = Spec 44</div> </div>	<div>Industry Standards:</div> <div> <div>? Government/Industry Qu</div> <div>? RoHS/ELV Compliance compliant</div> <div>? Lead Free Solder Proces lead free process</div> <div>? RoHS/ELV Compliance RoHS compliant</div> </div> <div>Conditions for Usage:</div> <div> <div>? Temperature Range (°C)</div> </div> <div>Operation/Application:</div> <div> <div>? Application = General Pu</div> </div> <div>Packaging Related Features:</div> <div> <div>? Wire Source = United Ki</div> <div>? Wire Size - Details = 2 0.00037 in ², 19 x 36 A</div> </div> <div>Other:</div> <div> <div>? Brand = Raychem</div> </div>

Languages

: English | [Deutsch](#) | [Español](#) | [Português \(do Brasil\)](#) | [???????](#) | [Italiano](#) | [????](#) | [\(?? \)](#)

Country Sites

: [China](#) | [Japan](#)